

MIGHTY HOOD & DOOR LATCH LUBRICANT 11 OZ. MN111

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 08/28/2014

Version:

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : MIGHTY HOOD & DOOR LATCH LUBRICANT 11 OZ.
Product code : MN111

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Lubricant

1.3. Details of the supplier of the safety data sheet

Mighty Auto Parts
650 Engineering Drive
Norcross, Georgia 30092
T 770-448-3900

1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Aerosol 1 H222
Compressed gas H280
Skin Irrit. 2 H315
Muta. 1B H340
Carc. 1A H350
Repr. 2 H361
STOT SE 3 H336
STOT RE 2 H373

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H222 - Extremely flammable aerosol
H280 - Contains gas under pressure; may explode if heated
H315 - Causes skin irritation
H336 - May cause drowsiness or dizziness
H340 - May cause genetic defects
H350 - May cause cancer
H361 - Suspected of damaging fertility or the unborn child
H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS-US) :

P201 - Obtain special instructions
P202 - Do not handle until all safety precautions have been read and understood
P210 - Keep away from heat, sparks, open flames, hot surfaces. - No smoking
P211 - Do not spray on an open flame or other ignition source
P251 - Pressurized container: Do not pierce or burn, even after use
P260 - Do not breathe dust, fumes, gas, mist, vapor spray
P261 - Avoid breathing dust, fume, gas, mist, vapor spray
P264 - Wash affected areas thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear protective gloves, protective clothing, eye protection, face protection
P302+P352 - If on skin: Wash with plenty of soap and water
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P308+P313 - If exposed or concerned: Get medical advice/attention
P312 - Call a POISON CONTROL CENTER, doctor, if you feel unwell.
P314 - Get medical advice/attention if you feel unwell
P321 - Specific treatment: See section 4.1 on SDS
P332+P313 - If skin irritation occurs: Get medical advice/attention

MIGHTY HOOD & DOOR LATCH LUBRICANT 11 OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P362 - Take off contaminated clothing and wash before reuse
P403+P233 - Store in a well-ventilated place. Keep container tightly closed
P405 - Store locked up
P410+P403 - Protect from sunlight. Store in a well-ventilated place
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F
P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

2.3. Other hazards

Other hazards not contributing to the classification : Contains gas under pressure; may explode if heated.

2.4. Unknown acute toxicity (GHS-US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

| Name | Product identifier | % | Classification (GHS-US) |
|--|----------------------|-----------------|---|
| Heptane, Branched Cyclic | (CAS No) 426260-76-6 | 47.328 - 49.3 | Flam. Liq. 1, H224 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 3, H412 |
| Heptane | (CAS No) 142-82-5 | 12.325 - 22.185 | Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 |
| Petroleum Gases, Liquefied, Sweetened | (CAS No) 68476-86-8 | 10 - 30 | Flam. Gas 1, H220 Flam. Liq. 1, H224 Muta. 1B, H340 Carc. 1A, H350 |
| Distillates (Petroleum), Hydrotreated Heavy Naphthenic | (CAS No) 64742-52-5 | 10 - 30 | Not classified |
| Distillates (Petroleum), Hydrotreated Heavy Naphthenic | (CAS No) 64742-52-5 | 10 - 30 | Acute Tox. 4 (Inhalation:dust,mist), H332 |
| Toluene | (CAS No) 108-88-3 | 0.493 - 1.972 | Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 |
| Oleic Acid | (CAS No) 112-80-1 | 1 - 5 | Not classified |

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medical advice/attention.

First-aid measures after inhalation : Cough. Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor/physician if you feel unwell.

First-aid measures after skin contact : Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact : Direct contact with the eyes is likely to be irritating. Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : May cause genetic defects. Suspected of damaging fertility or the unborn child. Causes damage to organs.

Symptoms/injuries after inhalation : Shortness of breath. May cause cancer by inhalation. May cause drowsiness or dizziness.

Symptoms/injuries after skin contact : Causes skin irritation.

Symptoms/injuries after eye contact : Causes eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

MIGHTY HOOD & DOOR LATCH LUBRICANT 11 OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Extremely flammable aerosol.
Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment. DO NOT fight fire when fire reaches explosives. Evacuate area.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.
Other information : Aerosol level 3.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : No naked lights. No smoking. Isolate from fire, if possible, without unnecessary risk. Remove ignition sources. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

- Protective equipment : Gloves. Safety glasses.
Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection. Avoid breathing dust,fume,gas,mist,vapor spray.
Emergency procedures : Ventilate area.

6.2. Environmental precautions

- Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- For containment : Dam up the liquid spill.
Methods for cleaning up : Store away from other materials.

6.4. Reference to other sections

- See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Hazardous waste due to potential risk of explosion. Pressurized container: Do not pierce or burn, even after use.
Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not spray on an open flame or other ignition source. Obtain special instructions . Do not handle until all safety precautions have been read and understood. Eliminate all ignition sources if safe to do so. Avoid breathing dust,fume,gas,mist,vapor spray. Use only outdoors or in a well-ventilated area.
Hygiene measures : Wash affected areas thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed.
Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep in fireproof place. Keep container tightly closed.
Incompatible products : Strong bases. Strong acids.
Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.
Storage area : Store in a well-ventilated place.

7.3. Specific end use(s)

- Follow Label Directions.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| Toluene (108-88-3) | | |
|--------------------|--------------------------------|----------------------|
| USA ACGIH | ACGIH TWA (mg/m ³) | 75 mg/m ³ |
| USA ACGIH | ACGIH TWA (ppm) | 20 ppm |
| USA OSHA | OSHA PEL (TWA) (ppm) | 200 ppm |
| USA OSHA | OSHA PEL (Ceiling) (ppm) | 300 ppm |

MIGHTY HOOD & DOOR LATCH LUBRICANT 11 OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| Heptane (142-82-5) | | |
|--------------------|------------------|---------|
| USA ACGIH | ACGIH TWA (ppm) | 400 ppm |
| USA ACGIH | ACGIH STEL (ppm) | 400 ppm |

| Heptane, Branched Cyclic (426260-76-6) | | |
|--|----------------------|---------|
| USA ACGIH | ACGIH TWA (ppm) | 400 ppm |
| USA ACGIH | ACGIH STEL (ppm) | 500 ppm |
| USA OSHA | OSHA PEL (TWA) (ppm) | 500 ppm |

| Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5) | | |
|---|-------------------------------------|----------------------------------|
| USA ACGIH | ACGIH TWA (mg/m ³) | 5 mg/m ³ MIST 8 HOURS |
| USA OSHA | OSHA PEL (TWA) (mg/m ³) | 5 mg/m ³ MIST 8 HOURS |

| Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5) | | |
|---|--------------------------------|--|
| USA ACGIH | ACGIH TWA (mg/m ³) | 5 mg/m ³ Inhalable fraction |

| Petroleum Gases, Liquefied, Sweetened (68476-86-8) | | |
|--|-------------------------------------|--|
| USA ACGIH | ACGIH TWA (ppm) | 1000 ppm Listed under Aliphatic hydrocarbon gases alkane C1-C4 |
| USA OSHA | OSHA PEL (TWA) (mg/m ³) | 1800 mg/m ³ |
| USA OSHA | OSHA PEL (TWA) (ppm) | 1000 ppm |

8.2. Exposure controls

Appropriate engineering controls : Local exhaust ventilation, vent hoods.
Personal protective equipment : Gloves. Safety glasses. Avoid all unnecessary exposure.



Hand protection : Wear protective gloves.
Eye protection : Chemical goggles or safety glasses.
Skin and body protection : Wear suitable protective clothing.
Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is recommended.
Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Gas
Appearance : Liquid.
Color : Colourless to yellow.
Odor : Solvent-like odour. Sweet.
Odor threshold : No data available
pH : No data available
Relative evaporation rate (butyl acetate=1) : No data available
Melting point : No data available
Freezing point : No data available
Boiling point : -31.1 °C (Lowest Component)
Flash point : -96.23 °C (Lowest Component)
Auto-ignition temperature : No data available
Decomposition temperature : No data available
Flammability (solid, gas) : No data available
Vapor pressure : No data available
Relative vapor density at 20 °C : No data available
Relative density : 0.76
Solubility : Insoluble in water.
Log Pow : No data available
Log Kow : No data available

MIGHTY HOOD & DOOR LATCH LUBRICANT 11 OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | |
|----------------------|---------------------|
| Viscosity, kinematic | : No data available |
| Viscosity, dynamic | : No data available |
| Explosive properties | : No data available |
| Oxidizing properties | : No data available |
| Explosive limits | : No data available |

9.2. Other information

| | |
|-------------|----------|
| VOC content | : 67.2 % |
|-------------|----------|

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Heat. Sparks. Open flame. Overheating.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

| Toluene (108-88-3) | |
|----------------------------|---|
| LD50 oral rat | 5580 mg/kg body weight (Rat; Equivalent or similar to OECD 401; Literature study; 5580 mg/kg bodyweight; Rat; Experimental value) |
| LD50 dermal rabbit | > 5000 mg/kg body weight LD50 quoted as 14.1 mL/kg (12267 mg/kg using density of 0.87) |
| LC50 inhalation rat (mg/l) | > 28.1 mg/l/4h (Rat; Air, Literature study) |

| Heptane (142-82-5) | |
|----------------------------|---|
| LD50 oral rat | > 15000 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; >5000 mg/kg bodyweight; Rat; Read-across) |
| LD50 dermal rabbit | > 3160 mg/kg (Rabbit; Literature study; Equivalent or similar to OECD 402; >2000 mg/kg bodyweight; Rabbit; Read-across) |
| LC50 inhalation rat (mg/l) | 103 mg/l/4h (Rat; Literature study) |
| LC50 inhalation rat (ppm) | 25000 ppm/4h (Rat; Literature study) |

| Heptane, Branched Cyclic (426260-76-6) | |
|---|---|
| LD50 oral rat | > 15000 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; >5000 mg/kg bodyweight; Rat; Read-across) |
| LD50 dermal rabbit | > 3160 mg/kg (Rabbit; Literature study; Equivalent or similar to OECD 402; >2000 mg/kg bodyweight; Rabbit; Read-across) |
| LC50 inhalation rat (mg/l) | 103 mg/l/4h (Rat; Literature study) |
| LC50 inhalation rat (ppm) | 25000 ppm/4h (Rat; Literature study) |

| Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5) | |
|--|--------------------------|
| LD50 oral rat | > 5000 mg/kg body weight |
| LD50 dermal rabbit | > 2000 mg/kg body weight |
| LC50 inhalation rat (mg/l) | > 5.2 mg/l/4h |

| Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5) | |
|--|--------------|
| LD50 oral rat | > 5000 ml/kg |
| LD50 dermal rabbit | > 2000 mg/kg |
| LC50 inhalation rat (mg/l) | 2.18 mg/l/4h |

| Oleic Acid (112-80-1) | |
|------------------------------|---------------------|
| LD50 oral rat | > 19200 mg/kg (Rat) |

MIGHTY HOOD & DOOR LATCH LUBRICANT 11 OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | |
|-----------------------------------|------------------------------|
| Skin corrosion/irritation | : Causes skin irritation. |
| Serious eye damage/irritation | : Not classified |
| Respiratory or skin sensitization | : Not classified |
| Germ cell mutagenicity | : May cause genetic defects. |
| Carcinogenicity | : May cause cancer. |

| | |
|---------------------------|---|
| Toluene (108-88-3) | |
| IARC group | 3 |

| | |
|--|---|
| Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5) | |
| IARC group | 3 |

| | |
|---|---|
| Reproductive toxicity | : Suspected of damaging fertility or the unborn child. |
| Specific target organ toxicity (single exposure) | : May cause drowsiness or dizziness. |
| Specific target organ toxicity (repeated exposure) | : May cause damage to organs through prolonged or repeated exposure. |
| Aspiration hazard | : Not classified |
| Potential Adverse human health effects and symptoms | : Based on available data, the classification criteria are not met. |
| Symptoms/injuries after inhalation | : Shortness of breath. May cause cancer by inhalation. May cause drowsiness or dizziness. |
| Symptoms/injuries after skin contact | : Causes skin irritation. |
| Symptoms/injuries after eye contact | : Causes eye irritation. |

SECTION 12: Ecological information

12.1. Toxicity

| | |
|---------------------------|--|
| Toluene (108-88-3) | |
| LC50 fish 1 | 24 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss) |
| EC50 Daphnia 1 | 84 mg/l (24 h; Daphnia magna; Locomotor effect) |
| LC50 fish 2 | 13 mg/l (96 h; Lepomis macrochirus) |
| EC50 Daphnia 2 | 11.5 - 19.6 mg/l (48 h; Daphnia magna) |
| Threshold limit algae 1 | > 400 mg/l (168 h; Scenedesmus quadricauda; Toxicity test) |
| Threshold limit algae 2 | 105 mg/l (192 h; Microcystis aeruginosa) |

| | |
|---|---|
| Heptane (142-82-5) | |
| LC50 fish 1 | 375 mg/l (96 h; Tilapia mosambica; Nominal concentration) |
| LC50 other aquatic organisms 1 | > 1000 mg/l (96 h) |
| EC50 Daphnia 1 | 1.5 mg/l (48 h; Daphnia magna) |
| LC50 fish 2 | > 100 mg/l (96 h; Oncorhynchus kisutch) |
| TLM fish 1 | 4924 mg/l (48 h; Gambusia affinis) |
| Threshold limit other aquatic organisms 1 | > 1000 mg/l (96 h) |
| Threshold limit algae 1 | > 200 mg/l (Scenedesmus quadricauda; Toxicity test) |
| Threshold limit algae 2 | 1.5 mg/l (8 h; Algae; Photosynthesis) |

| | |
|--|----------------------|
| Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5) | |
| EC50 Daphnia 1 | > 1000 mg/l 48 HOURS |

| | |
|---|---|
| Oleic Acid (112-80-1) | |
| LC50 fish 1 | 12 mg/l (33 h; Oncorhynchus kisutch) |
| LC50 fish 2 | 205 mg/l (96 h; Pimephales promelas) |
| Threshold limit other aquatic organisms 1 | < 40 mg/l (0.3 h; Echinoidea; Reproduction) |

12.2. Persistence and degradability

| | |
|--|------------------|
| MIGHTY HOOD & DOOR LATCH LUBRICANT 11 OZ. | |
| Persistence and degradability | Not established. |

| | |
|---------------------------------|--|
| Toluene (108-88-3) | |
| Persistence and degradability | Readily biodegradable in water. Biodegradable in the soil. Low potential for adsorption in soil. |
| Biochemical oxygen demand (BOD) | 2.15 g O ₂ /g substance |
| Chemical oxygen demand (COD) | 2.52 g O ₂ /g substance |
| ThOD | 3.13 g O ₂ /g substance |
| BOD (% of ThOD) | 0.69 % ThOD |

| | |
|-------------------------------|---|
| Heptane (142-82-5) | |
| Persistence and degradability | Readily biodegradable in water. Biodegradable in the soil. Adsorbs into the soil. |

MIGHTY HOOD & DOOR LATCH LUBRICANT 11 OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| Heptane (142-82-5) | |
|---------------------------------|------------------------------------|
| Biochemical oxygen demand (BOD) | 1.92 g O ₂ /g substance |
| Chemical oxygen demand (COD) | 0.06 g O ₂ /g substance |
| ThOD | 3.52 g O ₂ /g substance |
| BOD (% of ThOD) | > % ThOD (5 day(s)) > 0.5 |

| Heptane, Branched Cyclic (426260-76-6) | |
|---|---|
| Persistence and degradability | May cause long-term adverse effects in the environment. |

| Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5) | |
|--|------------------|
| Persistence and degradability | Not established. |

| Oleic Acid (112-80-1) | |
|-------------------------------|--|
| Persistence and degradability | Readily biodegradable in water. Biodegradable in the soil. Adsorbs into the soil. Photodegradation in the air. |
| Chemical oxygen demand (COD) | 2.25 g O ₂ /g substance |
| ThOD | 2.89 g O ₂ /g substance |
| BOD (% of ThOD) | > % ThOD (5 day(s)) > 0.5 |

| Petroleum Gases, Liquefied, Sweetened (68476-86-8) | |
|---|------------------|
| Persistence and degradability | Not established. |

12.3. Bioaccumulative potential

| MIGHTY HOOD & DOOR LATCH LUBRICANT 11 OZ. | |
|--|------------------|
| Bioaccumulative potential | Not established. |

| Toluene (108-88-3) | |
|-------------------------------|--|
| BCF fish 1 | 13.2 (Anguilla japonica) |
| BCF fish 2 | 90 (72 h; Leuciscus idus) |
| BCF other aquatic organisms 1 | 380 (24 h; Chlorella sp.; Fresh weight) |
| BCF other aquatic organisms 2 | 4.2 (Mytilus edulis; Fresh weight) |
| Log Pow | 2.73 (Experimental value; Other; 20 °C) |
| Bioaccumulative potential | Low potential for bioaccumulation (BCF < 500). |

| Heptane (142-82-5) | |
|-------------------------------|--|
| BCF other aquatic organisms 1 | 552 |
| Log Pow | 4.66 (Experimental value; 4.5; Literature) |
| Bioaccumulative potential | Potential for bioaccumulation (4 ≥ Log Kow ≤ 5). |

| Heptane, Branched Cyclic (426260-76-6) | |
|---|------------------|
| Bioaccumulative potential | Not established. |

| Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5) | |
|--|------------------|
| Bioaccumulative potential | Not established. |

| Oleic Acid (112-80-1) | |
|------------------------------|--------------------|
| Log Pow | 5.24 - 7.18 (QSAR) |
| Bioaccumulative potential | Not established. |

| Petroleum Gases, Liquefied, Sweetened (68476-86-8) | |
|---|------------------|
| Bioaccumulative potential | Not established. |

12.4. Mobility in soil

| Toluene (108-88-3) | |
|---------------------------|------------------|
| Surface tension | 0.03 N/m (20 °C) |

| Heptane (142-82-5) | |
|---------------------------|-------------------|
| Surface tension | 0.020 N/m (20 °C) |

| Oleic Acid (112-80-1) | |
|------------------------------|-------------------|
| Surface tension | 0.033 N/m (20 °C) |

12.5. Other adverse effects

Other information : Avoid release to the environment.

MIGHTY HOOD & DOOR LATCH LUBRICANT 11 OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 13: Disposal considerations

13.1. Waste treatment methods

- Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Container under pressure. Do not drill or burn even after use. Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.
- Additional information : Flammable vapors may accumulate in the container.
- Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

- US DOT (ground): UN1950, Aerosols, 2.1, Limited Quantity
- ICAO/IATA (air): UN1950, Aerosols, 2.1, Limited Quantity
- IMO/IMDG (water): UN1950, Aerosols, 2.1, Limited Quantity
- Special Provisions: N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.

14.2. UN proper shipping name

- Proper Shipping Name (DOT) : Aerosols
flammable, (each not exceeding 1 L capacity)
- Department of Transportation (DOT) Hazard Classes : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115
- Hazard labels (DOT) : 2.1 - Flammable gas



- DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.
- DOT Packaging Exceptions (49 CFR 173.xxx) : 306
- DOT Packaging Non Bulk (49 CFR 173.xxx) : None
- DOT Packaging Bulk (49 CFR 173.xxx) : None

14.3. Additional information

- Other information : No supplementary information available.

Overland transport

No additional information available

Transport by sea

- DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
- DOT Vessel Stowage Other : 48 - Stow "away from" sources of heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials

Air transport

- DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 75 kg
- DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg

SECTION 15: Regulatory information

15.1. US Federal regulations

MIGHTY HOOD & DOOR LATCH LUBRICANT 11 OZ.

| | |
|-------------------------------------|--|
| SARA Section 311/312 Hazard Classes | Delayed (chronic) health hazard Fire hazard Immediate (acute) health hazard Sudden release of pressure hazard |
|-------------------------------------|--|

Toluene (108-88-3)

| | |
|---|---|
| Listed on United States SARA Section 313 Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| SARA Section 311/312 Hazard Classes | Delayed (chronic) health hazard Fire hazard Immediate (acute) health hazard |

MIGHTY HOOD & DOOR LATCH LUBRICANT 11 OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | |
|---|---|
| Heptane, Branched Cyclic (426260-76-6) | |
| Not listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| SARA Section 311/312 Hazard Classes | Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard |
| Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5) | |
| SARA Section 311/312 Hazard Classes | Delayed (chronic) health hazard |
| Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| SARA Section 311/312 Hazard Classes | Immediate (acute) health hazard |
| Oleic Acid (112-80-1) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| Petroleum Gases, Liquefied, Sweetened (68476-86-8) | |
| SARA Section 311/312 Hazard Classes | Immediate (acute) health hazard Fire hazard Sudden release of pressure hazard |

15.2. International regulations

CANADA

| | |
|--|---|
| MIGHTY HOOD & DOOR LATCH LUBRICANT 11 OZ. | |
| WHMIS Classification | Class B Division 5 - Flammable Aerosol |
| Toluene (108-88-3) | |
| WHMIS Classification | Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects |
| Heptane, Branched Cyclic (426260-76-6) | |
| WHMIS Classification | Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects |
| Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5) | |
| Listed on the Canadian DSL (Domestic Substances List) | |
| Oleic Acid (112-80-1) | |
| Listed on the Canadian DSL (Domestic Substances List) | |

EU-Regulations

| | |
|--|--|
| Toluene (108-88-3) | |
| Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) | |
| Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5) | |
| Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) | |
| Oleic Acid (112-80-1) | |
| Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)- Directive 79/831/EEC, sixth Amendment of Directive 67/548/EEC (dangerous substances) | |

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Carc.Cat.1; R45

Muta.Cat.2; R46

Repr.Cat.3; R63

F+; R12

Xi; R38

Full text of R-phrases: see section 16

15.2.2. National regulations

MIGHTY HOOD & DOOR LATCH LUBRICANT 11 OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5)

Listed on AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Oleic Acid (112-80-1)

Listed on AICS (Australian Inventory of Chemical Substances)
Listed on the Korean ECL (Existing Chemicals List)

15.3. US State regulations

Toluene (108-88-3)

U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)

SECTION 16: Other information

Other information : None.

Full text of H-phrases: see section 16:

| | |
|-------------------------------------|---|
| Acute Tox. 4 (Inhalation:dust,mist) | Acute toxicity (inhalation:dust,mist) Category 4 |
| Aquatic Acute 1 | Hazardous to the aquatic environment - Acute Hazard Category 1 |
| Aquatic Chronic 1 | Hazardous to the aquatic environment - Chronic Hazard Category 1 |
| Aquatic Chronic 3 | Hazardous to the aquatic environment - Chronic Hazard Category 3 |
| Asp. Tox. 1 | Aspiration hazard Category 1 |
| Carc. 1A | Carcinogenicity Category 1A |
| Compressed gas | Gases under pressure Compressed gas |
| Flam. Aerosol 1 | Flammable aerosol Category 1 |
| Flam. Gas 1 | Flammable gases Category 1 |
| Flam. Liq. 1 | Flammable liquids Category 1 |
| Flam. Liq. 2 | Flammable liquids Category 2 |
| Muta. 1B | Germ cell mutagenicity Category 1B |
| Repr. 2 | Reproductive toxicity Category 2 |
| Skin Irrit. 2 | Skin corrosion/irritation Category 2 |
| STOT RE 2 | Specific target organ toxicity (repeated exposure) Category 2 |
| STOT SE 3 | Specific target organ toxicity (single exposure) Category 3 |
| H220 | Extremely flammable gas |
| H222 | Extremely flammable aerosol |
| H224 | Extremely flammable liquid and vapor |
| H225 | Highly flammable liquid and vapor |
| H280 | Contains gas under pressure; may explode if heated |
| H304 | May be fatal if swallowed and enters airways |
| H315 | Causes skin irritation |
| H332 | Harmful if inhaled |
| H336 | May cause drowsiness or dizziness |
| H340 | May cause genetic defects |
| H350 | May cause cancer |
| H361 | Suspected of damaging fertility or the unborn child |
| H373 | May cause damage to organs through prolonged or repeated exposure |
| H400 | Very toxic to aquatic life |
| H410 | Very toxic to aquatic life with long lasting effects |
| H412 | Harmful to aquatic life with long lasting effects |

NFPA health hazard


: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard

: 3 - Liquids and solids that can be ignited under almost all ambient conditions.

NFPA reactivity

: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



MIGHTY HOOD & DOOR LATCH LUBRICANT 11 OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

HMIS III Rating

| | |
|---------------------|---|
| Health | : 2 Moderate Hazard - Temporary or minor injury may occur |
| Flammability | : 3 Serious Hazard |
| Physical | : 1 Slight Hazard |
| Personal Protection | : B |

SDS US (GHS HazCom 2012) - TCC

The Supplier identified in Section 1 of this MSDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product

Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.