



HIGH TEMP RED

IN-EIC-F-06 REV 0 16 DE OCTUBRE DEL 2019
LAST UPDATE: MARCH 2020

MSDS: 1510712

COMPANY INFORMATION

Manufacturer	Lubricantes de América, S.A. de C.V.
Emergency Phone	(52) 81 81 22 74 00
Address	Carretera a García Km 1.2 Int. 8, Santa Catarina, N.L. C.P. 66350

I.- PRODUCT IDENTIFICATION

Product Name	HIGH TEMP RED
Process	LUBRICANT
Synonyms	LUBRICANT GREASE

II.- IDENTIFICATION OF DANGER OR DANGERS

DANGER RANGE	HEALTH	FIRE	REACT	SPECIAL
NFPA	1	1	0	///
HMIS	1	1	0	///

PRODUCT LISTED IN NOM-052-SEMARNAT-2005 YES__ NO X

Word of warning: Attention

- P101: If you need to consult a doctor: have the container or product label on hand.
- P202: Do not handle the substance before reading and understanding all safety instructions.
- P301: In case of ingestion.
- P310: Immediately call a poison control center or doctor.
- P305: In case of eye contact
- P351: Rinse with water carefully for several minutes
- P338 Remove contact lenses, when present and can be easily made. Pursue with the washing.
- P402: Store in a dry place.
- P501: Delete the content / container.



- H227: Combustible liquid.
- H317: May cause an allergic skin reaction.
- H319: Causes serious eye irritation / causes eye irritation (2A).
- H412: Harmful to aquatic organisms with long-lasting harmful effects

III.- COMPOSITION / INFORMATION ON INGREDIENTS

Name of Chemical Base:	Hydrocarbon
Chemical Family:	Hydrocarbon
Molecular Formula:	N/D



HIGH TEMP RED

Chemical Name	No. CAS	% Vol.	Exp. limits
Additive package	Mixture	< 5	TLV 5 mg/m ³
Lithium hydroxystearate	1370-86-6	< 15	TLV 5 mg/m ³
Petroleum distilled, hydrotreated naphthenic	64742-52-5	< 90	TLV 10 mg/m ³
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8		
Distillates (petroleum), hydrotreated light paraffinic	64742-54-7		

****Ref. STPS-CPT OSHA-PEL ACGIH-TLV**

IV.- FIRST AID

INHALATION: Remove the victim from the source of exposure. Get medical attention if irritation persists.
EYES: Immediately flush with large amounts of water for 15 minutes, keeping eyelids are sections of ocular cell to ensure a thorough washing.
SKIN: Remove contaminated clothing immediately and wash the area thoroughly with soap and water
INGESTION: No Do not induce vomiting. If spontaneous vomiting occurs monitored for respiratory distress and obtaining medical care.
DATA FOR MEDICAL DOCTOR: The possible aspiration of petroleum products of high viscosity is very mild; the petroleum products may cause severe pneumonitis (oil pneumonia) when considering instituting gastric lavage should be considered in unconscious victims the use of an endotracheal tube.

V.- FIRE FIGHTING MEASURES

Flash Point (ASTM D-92)	>220 °C
Flammability (Explosive) Limits:	N. A
Lower	N. A
Upper	N. A
EXTINGUISHING MEDIA	
PQS	X
CO2	X
FOAM	X
WATER	X

FIRE FIGHTING PROCEDURE:

Use water fog to cool the containers and exposed structures to protect people. Use water to remove and take away from ignition sources from the product. Don't throw to the sewer system.

PERSONAL PROTECTION EQUIPMENT

Use normal fire fighter suit.

COMBUSTION PRODUCTS

During Thermal decomposition could be formed toxics and irritating substances. Firefighter must use protector equipment and gas mask.

N.A. - Non applicable N.D. - Non determinated | N.E. – Non established

VI.- MEASURES TO TAKE IN CASE OF ACCIDENTAL SPILL

GENERAL: Stop leak if possible, without risk.
SMALL LEAK: Collect with sand or other non-combustible absorbent material and place in containers for later discarding.
LARGE SPILL: Construct a dike ahead of liquid spill for later disposal.

DISPOSAL METHOD: This substance, when discarded or disposed is not specifically included as hazardous waste in federal regulations, however, may be characteristically hazardous if it is considered toxic, flammable, corrosive or reactive according to federal definitions. This substance can also become dangerous when mixed or has contact with hazardous wastes.

VII.- HANDLING AND STORAGE

CAUTIONS: Avoid extremes of temperature during storage
MANAGEMENT: For stowing and storing drums use forklift or hoist.
STORAGE: In sealed containers in a cool, dry, isolated, ventilated away of ignition sources and incompatible materials. not stored in containers not labeled, do not eat, drink or smoke in areas of use or storage

VIII.- EXPOSURE CONTROL/PERSONAL PROTECTION

VENTILATION: Open
BREATHING: If you feel irritation you should use (NIOSH) approved respiratory protection (masks Antigen)
EYES: Wear safety glasses or goggles and provide an eyewash station in work area. Do not use contact lenses when working with this substance.
GLOVES AND CLOTHING: Wear appropriate protective gloves for chemicals



OTHER PROTECTIVE EQUIPMENT: Face masks, apron cover arms, etc.

IX.- PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Semi-solid	Freeze point:	N.D.
Color	Amber	Relative density (water = 1)	0.87
Odor	Hydrocarbon	Water solubility	Insoluble
Molecular weight	N.D.	Vapor density (air=1)	< 1
pH:	N.D.	Vapor pressure (mm Hg):	< 1
Viscosity:	N.D.	Flash point:	>220
Boiling point:	N.A.		

N.A. - Non applicable | N.D. – Non data

X.- STABILITY AND REACTIVITY

Stability:	Stable
Conditions to avoid:	Contact with strong oxidizers
Hazardous polymerization:	Not possible
Non compatible materials:	Oxidizer materials
Hazardous decomposition products:	combustion of the product can form CO ₂ , and active hydrocarbons

XI.- TOXICOLOGICAL INFORMATION

PRIMARY EXPOUSURE ROUTES:

ACUTE EXPOSITION EFFECTS: Could be irritant to skin, eyes and respiratory system.

INHALATION: the product can cause irritation in respiratory track; exposition to high concentrations can cause oil pneumonia

EYES: LITTLE IRRITANT. The contact with hot material can cause burns.

SKIN: LITTLE IRRITANT, THE CONTINUOUS OR PROLONGED CONTACT CAN CAUSE DERMATITIS

INGESTION: CAN CAUSE GASTROINTESTINAL PROBLEMS

TOXICITY:

DL50>500 mg/kg (oral): practically non-toxic
 DL50> 500 mg/kg (Dermal): practically non-toxic
 CL50> 500 mg/m³ (Inhalación): practically non-toxic
 Irritant doce of eyes: Not irresistible

XII.- ECOTOXICOLOGICAL INFORMATION

Dispose in accordance with applicable local, state, and federal regulations.

XIII.- INFORMATION REGARDING THE DISPOSAL OF PRODUCTS

CONCERNING THE PACKAGE: The method of disposal of packaging will be provided by the user in accordance with applicable laws and regulations, according to the product characteristics

Product listing on NOM-052 SEMARNAT-2005 YES ___ NO X

CONCERNING THE CONTENT: The contents of the package must be disposed of according to local, state or federal regulations, as applicable.

XIV.- INFORMATION REGARDING TRANSPORT

Transport Name	Lubricant Grease
IDENTIFICATION NUMBER (UN):	N. A
DANGER CLASSIFICATION:	N. A
ANSWER GUIDE No DOT:	N. A



XV.- REGULATORY INFORMATION

15.1. Safety, health, and environmental regulations/legislation specific for the substance or mixture.

Statutory Instruments. It covers Nom-028-STPS-2012 and NOM-056-SSA1-2012.

XVI.- ADITIONAL INFORMATION

Information related to this product may not be valid if it is used in combination with other materials or in other processes. Users are responsible for the interpretation and application of this information for their own use.

CAS	Chemical Abstract Services
Lim. Exp.	Exposure Limit
°C	Degree Celsius
N/A	Not Applicable
N/D	Not Available
NIOSH	National Institute for Occupational Safety and Healthy
cSt	Centistokes
CL50	Lethal Concentration Average

DL50	Median Lethal Dose
DOT	USA (Department of Transportation)
pH	Potential Hydrogen
% Vol.	Volume percent (Vol %)
mg/m ³	Milligrams per cubic meter, Concentration unit.
mmHg	Millimeters of Mercury