



SAFETY DATA SHEET

Section 1: Identification

Product Name: Mighty Ceramic Coating
Product Code: DL6015
Product Class: Exterior Finish Coating
Manufacturer/Supplier: Mighty Distributing System of America
650 Engineering Drive
Norcross, GA 30092
Telephone: 800-829-3900
Emergency Telephone: CHEMTREC 800-424-9300

Date Prepared: October 30, 2018
Date of Review/Update:

Section 2: Hazard Identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200:

GHS Hazard Symbols:



GHS Classification: Aspiration Hazard Category 1; Flammable Liquid Category 2; Eye Damage/Irritation Category 2A; Specific Target Organ Toxicity – Repeated Exposure Category 3

Signal Word: Danger

GHS Hazard Statements:

H255 Highly flammable liquid and vapor
H304 May be fatal if swallowed and enters airways
H315 Causes skin irritation
H336 May cause drowsiness or dizziness

GHS Precautionary Statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking
P233 Keep container tightly closed
P240 Ground/bond container and receiving equipment
P241 Use explosion-proof electrical/ventilating/lighting/equipment
P242 Use only non-sparking tools
P243 Take precautionary measures against static discharge
P280 Wear protective gloves/protective clothing/eye protection/face protection
P264 Wash hands thoroughly after handling
P261 Avoid breathing dust/fumes/gas/mist/vapors/spray
P271 Use only outdoors or in well-ventilated areas
P301+P310 IF SWALLOWED: Immediately call a poison center or doctor
P331 Do NOT induce vomiting
P303+P361+P353 If on skin (or hair): Remove immediately all contaminated clothing. Rinse skin with water
P370+P378 In case of fire: use water spray, carbon dioxide, dry chemical or alcohol foam for extinction
P304 +P340 If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing
P312 Call a poison center or doctor if you feel unwell
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up
P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations.

Signs and Symptoms of Exposure:

Eye: Irritation including tearing or redness.
Skin: Prolonged skin contact may cause irritation including redness, irritation, itching.
Ingestion: May cause gastrointestinal irritation
Inhalation: None are known
Medical Conditions Aggravated by Exposure: None known.

Section 3: Composition/Information on Ingredients

<u>Chemical Name</u>	<u>CAS Number</u>	<u>% Range</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>
NAPTHA (petroleum) hydrotreated heavy	64742-48/9	75-80	TWA 100 ppm	
Distillates (petroleum) hydrotreated light	64742-47-8	5-10	TWA 165 ppm	
Pentaoxapentadecane	143-24-8	5	n/a	
Amyl Acetate	628-63-7	5-8	TWA 100 ppm	

Section 4: First Aid Measures

Eye Contact: Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.
 Skin Contact: Wash with soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing before reuse. Destroy or thoroughly clean contaminated shoes.
 Ingestion: Never give anything by mouth to an unconscious person. If person is conscious then give several glasses of water. Do not induce vomiting. Keep warm and quiet. Seek medical attention.
 Inhalation: Move to fresh air. Treat symptomatically. Get medical attention if symptoms persist,

Section 5: Fire-Fighting Measures

General fire hazards: Flammable liquid and vapor. USE WATER WITH CAUTION. Material will float and may ignite on surface of water. Use water spray to keep fire-exposed containers cool.
 Fire and Explosive Properties: Flash Point: 44°C / TCC Flammable Limits: LEL / UEL: No Data
 Extinguishing Media: Water spray, dry chemical, carbon dioxide, alcohol foam
 Special hazards arising from the substance: Vapors may cause a flash fire or ignite explosively. Vapors may travel considerable distance to a source of ignition and flash back. Prevent buildup of vapors or gases to explosive concentrations.
 Special Fire Fighting Procedures: Full protective equipment including self contained breathing apparatus for confined areas. Water may be ineffective in fighting the fire. Use water spray to keep fire exposed containers cool.

Section 6: Accidental Release Measures

Steps to be taken if Material is Spilled or Leaked: Eliminate the sources of ignition. Absorb spills with vermiculite or other inert material, then place in a container for chemical waste. Larger spills use water spray to disperse vapors and dilute spill to a non-flammable mixture. Prevent any runoff from entering any drains, sewers or streams. Dike for later disposal.
 Notification procedures: in the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Section 7: Handling and Storage

Precautions to be taken in Handling and Storage:
 Avoid breathing mist or vapors. Avoid contact with eyes and prolonged or repeated contact with skin. Use only with adequate ventilation. Wash hands thoroughly after handling. Keep container tightly closed and in a well-ventilated place. Affix proper warning labels on containers in accordance with 29CFR 1010.1200.

Section 8: Exposure Controls and Personal Protection

Ventilation: Use only with adequate ventilation. Avoid breathing vapor or mist. Local exhaust preferred.
 Respirator Protection: Properly fitted NIOSH/MSHA approved respirator for ingredients found in SECTION 3 if TLV is exceeded.
 Skin Protection: Gloves rated for protection against ingredients in SECTION 3.
 Eye Protection: Safety glasses with side shields or chemical goggles.

Section 9: Physical and Chemical Properties

Boiling Point: 155°C	Vapor Pressure (mmHg @ 68°F):	Unknown
Vapor Density: 5 (air=1)	Solubility in Water:	Complete
Specific Gravity: 1.01 ± 0.05	Melting Point:	Not Applicable
Appearance/Odor: Clear liquid, mild hydrocarbon odor	pH:	Not Applicable

Section 10: Stability and Reactivity

Stability: Stable
 Hazardous Polymerization: Will not occur.
 Hazardous Decomposition Products: Various hydrocarbons of incomplete combustion.
 Materials to Avoid: Strong oxidizers
 Conditions to Avoid: Open flames, sources of ignition.

Section 11: Toxicology Information

IARC, NTP, OSHA Carcinogen: None
 Information on likely routes of exposure:
 Inhalation: may cause drowsiness or dizziness
 Ingestion: none known

Skin contact: prolonged or repeated skin contact may cause drying, cracking, or irritation
Eye contact: causes serious eye irritation

Information on toxicological effects:

Acute Toxicity

Oral product: oral LD-50: rat; 6750 mg/kg
Dermal product: dermal LD-50: rat; >20 ml/kg
Inhalation product: LC50: rat; 8h: 50.6 mg/l
Repeated dose toxicity product: noael: rat, oral study, 90 days: 90 mg/kg
Skin corrosion/irritation product: guinea pig, 4h: slight
Respiratory or skin sensitization product: skin sensitization: guinea pig: non-sensitizing

Section 12: Ecological Information

All work practices must be aimed at eliminating environmental contamination.

Effects of material on plants and animals: This product may be harmful or fatal to plants and animal life if released into the environment.

Effect of material on aquatic life: The most sensitive known aquatic group to any component of this product is: Fish: LC-50 (golden orfe, 48h): 265-360 mg/l

Keep out of sewers and natural water supplies. This material is a mobile liquid.

Degradability: 76% (20 days, ready biodegradability: closed bottle test.) Readily biodegradable. This product does not accumulate or bio magnify in the environment.

Section 13: Disposal Considerations

Waste Disposal: Dispose of in accordance with federal, state, and local regulations.

Section 14: Transport Information

D.O.T. REQUIREMENTS (49CFR 172.101):

Shipping Description, UN1866, Resin Solution, 3 II

Section 15: Regulatory Information

RQ (REPORTABLE QUANTITY) 49CFR 172.101:

None

TSCA (Toxic Substances Control Act) Status:

The intentional ingredients of this product are listed.

CERCLA RQ - 40CFR 302.4:

None

SARA 302 COMPONENTS - 40CFR 355 Appendix A:

Immediate (acute) health hazard fire hazard

SECTION 311/312 HAZARD CLASS - 40CFR 370.2

Immediate (X)

Reactive ()

Delayed (X)

Sudden Release of Pressure ()

Fire (X)

SARA 313 COMPONENTS - 40CFR 372.65:

None

WORKPLACE HAZARDOUS INFORMATION SYSTEM (WHMIS)

<u>Ingredient</u>	<u>Max. % By Wt.</u>	<u>LD50</u>	<u>LC50</u>
NAPTHA (petroleum) hydrotreated heavy	75-80		
Distillates (petroleum) hydrotreated light	5-10		
Pentaoxapentadecane	5		
Amyl Acetate	5-8		

CALIFORNIA PROPOSITION 65:

None

Section 16: Other Information

Although the information contained herein is believed to be reliable, it is furnished without warranty of any kind. This information is not intended to be all-inclusive as to the manner and conditions of use, handling, and storage.