

Full Synthetic Gear Oils

Mighty Engine Guard Full Synthetic Gear Oils with Limited Slip additives provide unsurpassed advantages that exceed the capabilities of conventional lubricants. Engine Guard Synthetic Lubricants offer longer life and can extend equipment life because of the robust base stocks and specifically matched additive components. Contains only high-quality paraffinic lubricating oils and the most technologically advanced additive system, which includes extreme pressure, anti-wear, anti-friction agents, oxidation and corrosion inhibitors.




Non-Longitude



www.MightyAutoParts.com

Available Package Sizes



Full Synthetic Gear Oils

Typical Properties

Viscosity Grade		75W-90 Full Syn	75W-140 Full Syn
Brookfield Viscosity at -40°C, cP	ASTM D2983	135,000	127,000
Color	ASTM D1500	1	1
Flash Point °C	ASTM D92	224	232
Flash Point °F	ASTM D92	435	450
Gravity, °API	ASTM D287	31.24	34.31
Pour Point °C (°F)	ASTM D5950	-51°C (-60°F)	-51°C (-60°F)
Specific Gravity @ 60°F (15.6°C)	ASTM D4052	0.8695	0.8534
Viscosity @100°C cSt	ASTM D445	16.15	27.64
Viscosity @40°C cSt	ASTM D445	109.3	171.8
Viscosity Index	ASTM D2270	159	200

Industry/OEM Approvals

75W-90 Full Syn	75W-140 Full Syn
Meets Requirements	Meets Requirements
Meets Requirements	Meets Requirements
Meets Requirements	Meets Requirements
Suitable for Use	-
Suitable for Use	Suitable for Use
Meets Requirements	Meets Requirements
Meets Requirements	Meets Requirements
Meets Requirements	Meets Requirements
-	Meets Requirements
	 Meets Requirements Meets Requirements Meets Requirements Suitable for Use Suitable for Use Meets Requirements Meets Requirements