



ENEOS USA Inc.
[E'-ne-ohs]

SAFETY DATA SHEET

SDS: A4308-E231US+

Date Prepared: 2023/03/27

Date Revised:

Product Name: ENEOS X PRIME ENGINE OIL 0W-8

1. Identification

Product name: ENEOS X PRIME ENGINE OIL 0W-8
 Manufacturer/Supplier: ENEOS USA, Inc.
 Address: 20 North Martingale Road, Suite 325, Schaumburg, IL. 60173
 Charge section: Lubricants Sales Group
 TEL (Information): +1-847-413-2188
Emergency Telephone 3E: 1-800-451-8346
Number (US and Canada): ID Number: 17406
 Contact Available: 24/7/365
 Recommended use and restrictions on use: General industrial application

2. Hazards identification

Classification of the chemical in accordance with OSHA Hazard Communication Standard
 (29 CFR § 1910.1200)

Hazard category	Category
Flammable liquids	No Classification
Acute toxicity (oral)	No Classification
Acute toxicity (dermal)	No Classification
Acute toxicity (dust, mist)	No Classification
Skin corrosion/irritation	No Classification
Serious eye damage/eye irritation	No Classification
Aspiration hazard	No Classification
Acute hazards to the aquatic environment	Category 3
Chronic hazards to the aquatic environment	No Classification

Label elements

Pictograms: Not applicable
 Signal word: Not applicable
 Hazard statement: Harmful to aquatic life
 Precautionary statements:
 Prevention Do not handle until all safety precautions have been read and understood.
 Wear protective gloves/protective clothing/eye protection/face protection.



ENEOS USA Inc.
[E'-ne-ohs]

SAFETY DATA SHEET

SDS: A4308-E231US+

Date Prepared: 2023/03/27

Date Revised:

Product Name: ENEOS X PRIME ENGINE OIL 0W-8

Do not allow the eyes to become exposed to the product. Do not swallow the product.

Avoid release to the environment.

Wash hands thoroughly after handling.

Do not eat, drink or smoke when using this product.

Response IF SWALLOWED: Immediately call a POISON CENTER/doctor.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If the eyes are exposed to the product: Rinse the eyes with plenty of running water and immediately contact a physician.

IF ON SKIN: Wash with plenty of soap and water.

Storage The product must be stored in a cool, well-ventilated location where it will not be exposed to direct sunlight.

Containers that have been opened must be tightly sealed.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

If there are any doubts about proper methods of handling the product, contact the point of purchase before proceeding with usage.

Emergency overview: PBT or vPvB : Not applicable

3. Composition/information on ingredients

3.1 Substances Not Applicable

3.2 Mixtures

Ingredients and Concentration

Chemical Name	Concentration wt. %	CAS#
Base Oil(s)	80-90	Trade Secret
Additives	<20	
Oleoyl sarcosine	0.1-0.9	Trade Secret
Mixture of Molybdenum dialkyl dithio carbamate	0.1-0.9	Trade Secret



ENEOS USA Inc.
[E'-ne-ohs]

SAFETY DATA SHEET

SDS: A4308-E231US+

Date Prepared: 2023/03/27

Date Revised:

Product Name: ENEOS X PRIME ENGINE OIL 0W-8

4. First-aid measures

Inhalation:	If inhaled: Remove person to fresh air and keep comfortable for breathing. Cover the body with blankets to keep warm and quiet. If you feel unwell, seek medical advice.
Skin contact:	Immediately flush skin with large amounts of water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.
Eye contact:	Rinse with clean water carefully for several minutes. Remove contact lenses if present and if removal is easy, then continue rinsing. Rinse for 15 minutes at a minimum and seek medical attention.
Ingestion:	Do not induce vomiting. Drink [one glass] [two glasses] of water. Call a physician [or poison control center] immediately.
Most important symptoms/effects, acute and delayed.	May cause allergic skin reaction. Dermatis. Rash.
Protection for first aid person:	No information.

5. Fire-fighting measures

Suitable extinguishing media:	Mist of loaded liquid, dry chemicals, carbon dioxide, fire foam, and dry sand are effective.
Unsuitable extinguishing media:	Use of straight stream of water can cause a risk of spreading fire.
Specific hazards arising from the chemical:	In some cases of fire, may release irritant gases. When burnt, may generate carbon monoxide and other toxic gases.
Specific extinguishing methods:	Spray water to the surrounding facilities for cooling. Keep unauthorized persons off the site of occurrence of fire and the surroundings. Even after extinction, cool containers thoroughly with plenty of water.
Special protective equipment and precautions for fire fighters:	Wear fire/flame resistant/retardant clothing.



ENEOS USA Inc.
[E'-ne-ohs]

SAFETY DATA SHEET

SDS: A4308-E231US+

Date Prepared: 2023/03/27

Date Revised:

Product Name: ENEOS X PRIME ENGINE OIL 0W-8

Fight fire from windward direction while wearing protective equipment. If contact with skin is expected, wear impervious protective equipment and gloves.

Use air-breathing apparatus and protective clothing whenever necessary.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Wear protective equipment when working.

Remove nearby potential ignition sources immediately.

When mist is generated, use respiratory equipment to prevent inhalation of mist.

Do not touch or walk through spillage.

Pay attention to the site of spillage, which is slippery.

Environmental precautions:

Avoid release to the environment.

Prevent spreading of oil spill with earth and sand, sandbags, or other proper materials and use care not to allow the oil spill to flow to street drains, sewer systems, and rivers.

Methods and materials for containment and cleaning up:

In case of spillage in small quantity, collect spillage by absorbing with earth, sand, sawdust, waste, or other proper materials.

In case of spillage in large quantity, enclose with embankment to prevent spreading of spillage and collect spillage in empty containers to the extent possible.

Prevention of second accident:

In case of spillage, immediately inform the organizations concerned of the spillage to prevent possible accidents and spreading of spillage.

Remove nearby potential ignition sources immediately and make fire-extinguishing agents available. Remove spillage completely, and ventilate and clean the site and the surroundings.

7. Handling and storage



ENEOS USA Inc.
[E'-ne-ohs]

SAFETY DATA SHEET

SDS: A4308-E231US+

Date Prepared: 2023/03/27

Date Revised:

Product Name: ENEOS X PRIME ENGINE OIL 0W-8

Handling

- Technical measures: Keep away from any possible contact with sparks, open flames, and high-temperature materials, and do not allow release of vapor without justification.
- Use pumps or other proper equipment for taking out from containers. Do not siphon with your mouth using a tube. Do not drink.
- When mist is generated, use respiratory equipment to prevent inhalation of mist.
- In case of vapor/mist dispersion, install a closed system, local ventilation system, and/or other proper equipment for the sources of vapor/mist generation.
- Avoid rough handling of containers such as falling, dropping, exposing to shock, and dragging.
- Ventilation requirements: Maintain adequate ventilation when handling indoors.
- Precautions for safe handling: Avoid falling, dropping, exposing to shock, or dragging of containers.
- Wash hands and face thoroughly after handling.
- Be careful with fire.
- Wear protective gloves when opening containers to eliminate a risk of hand injury.
- Contact avoidance: Use care to keep away from any possible contact with halogens, strong acids, alkalis, and acidifying substances.
- Contact with and storage in the same location of halogens, strong acids, alkali and oxidized substances must be avoided.
- Hygiene measures: After handling Wash hands thoroughly.

Storage

- Storage conditions: Store in a well ventilated, cool, dry, dark place, protecting from direct sunlight and keeping away from any potential ignition sources and high-temperature materials.
- Store tightly stopped after use to prevent possible contamination with dust and moisture.
- Preferably store locked up in a proper storage area.
- Safety adequate container materials: Use spill-proof containers that are free of damage/corrosion.



ENEOS USA Inc.
[E'-ne-ohs]

SAFETY DATA SHEET

SDS: A4308-E231US+

Date Prepared: 2023/03/27

Date Revised:

Product Name: ENEOS X PRIME ENGINE OIL 0W-8

8. Exposure controls/personal protection

Appropriate engineering controls: In case of mist generation, enclose the source of mist generation, or install a ventilation system.

Install eye cleaning and body cleaning equipment near the handling site.

Control parameters

Chemical Name	U. S. - OSHA			ACGIH	
	Ceiling	STEL	TWA	TLV-STEL	TLV-TWA
Base Oil(s)	-ppm -mg/m3	-ppm -mg/m3	-ppm -mg/m3	-ppm -mg/m3	-ppm 5mg/m3 (Mineral Oil Mist)
Oleoyl sarcosine	-ppm -mg/m3	-ppm -mg/m3	-ppm -mg/m3	-ppm -mg/m3	-ppm -mg/m3
Mixture of Molybdenum dialkyl dithio carbamate	-ppm -mg/m3	-ppm -mg/m3	-ppm -mg/m3	-ppm -mg/m3	-ppm -mg/m3

Personal protective equipment

Respiratory protection: Not needed under normal conditions, but wear a gas mask (against organic gases) whenever required.

Hand protection: In case of prolonged or repeated exposure, wear oil-resistant hand protection.

Eye/face protection: In case of exposure to splashes, wear ordinary type goggles.

Skin protection: In case of handling over a prolonged period of time or in case of exposure to oil, wear oil-resistant, long-sleeved work clothing.

Hygiene measures: Take off contaminated clothing and wash thoroughly before reuse.

Wash hands thoroughly after handling.

9. Physical and chemical properties

Product

Appearance: Liquid



ENEOS USA Inc.
[E'-ne-ohs]

SAFETY DATA SHEET

SDS: A4308-E231US+

Date Prepared: 2023/03/27

Date Revised:

Product Name: ENEOS X PRIME ENGINE OIL 0W-8

Form:	Liquid
Color:	Light brown
Odor:	Slight odor
Melting point/freezing point:	Pour Point $\leq -35(^{\circ}\text{C})$
Initial boiling point and boiling range:	No data
Flammability (solid, gas):	No data
Upper/lower flammability or explosive limits:	No data
Flash point:	$\geq 200(^{\circ}\text{C})$ Cleveland Open Cup
Auto-ignition temperature:	Estimate 200—410 ($^{\circ}\text{C}$)
Decomposition temperature:	No data.
pH:	No data
Kinematic viscosity:	$> 20.5 (\text{mm}^2/\text{sec}) (40^{\circ}\text{C})$
Solubility:	water : Insoluble.
Partition coefficient: n-octanol/water:	No data.
Vapor pressure:	No data
Density (g/cm ³):	0.847 (15 $^{\circ}\text{C}$)
Vapor density:	No data.
Particle characteristics:	No data
Relative density:	No data.
Viscosity:	No data.

10. Stability and reactivity

Reactivity: Stable when stored or preserved in a dark place at room temperature.

Chemical stability: Stable when stored or preserved in a dark place at room temperature.

Possibility of hazardous reactions: Keep away from any possible contact with strong oxidizing agents.



ENEOS USA Inc.
[E'-ne-ohs]

SAFETY DATA SHEET

SDS: A4308-E231US+

Date Prepared: 2023/03/27

Date Revised:

Product Name: ENEOS X PRIME ENGINE OIL 0W-8

Conditions to avoid: Contact with incompatible hazard substances
Prolonged heating, open flames, and ignition sources

Incompatible materials: Use care to keep away from any possible contact with halogens, strong acids, alkalis, and acidifying substances.

Hazardous decomposition products: When burnt, may release carbon monoxide and other gases.

11. Toxicological information

Symptoms related to the physical, chemical and toxicological characteristics: May cause allergic skin reaction. Dermatitis. Rash.

Delayed and immediate effects and also chronic effects from short- and long- term exposure:

Short term exposure:
Potential immediate effects : No information
Potential delayed effects : No information

Long term exposure:
Potential immediate effects : No information
Potential delayed effects : No information

Product

Acute toxicity (oral): No Classification
For mixtures, hazard category was identified based on the classification criteria for mixtures.

Acute toxicity (dermal): No Classification
For mixtures, hazard category was identified based on the classification criteria for mixtures.

Acute toxicity (inhalation): Classification not possible (Gas)
Classification not possible (Vapor)
No Classification (Dust/Mist)
For mixtures, hazard category was identified based on the classification criteria for mixtures.

Skin corrosion/irritation: No Classification
For mixtures, hazard category was identified based on the classification criteria for mixtures.

Serious eye damage/irritation: No Classification



ENEOS USA Inc.
[E'-ne-ohs]

SAFETY DATA SHEET

SDS: A4308-E231US+

Date Prepared: 2023/03/27

Date Revised:

Product Name: ENEOS X PRIME ENGINE OIL 0W-8

For mixtures, hazard category was identified based on the classification criteria for mixtures.

Respiratory sensitization: Classification not possible

For mixtures, hazard category was identified based on the classification criteria for mixtures.

Skin sensitization: Classification not possible

For mixtures, hazard category was identified based on the classification criteria for mixtures.

Mutagenicity: Classification not possible

For mixtures, hazard category was identified based on the classification criteria for mixtures.

Carcinogenicity: Classification not possible

For mixtures, hazard category was identified based on the classification criteria for mixtures.

Reproductive toxicity: Classification not possible

For mixtures, hazard category was identified based on the classification criteria for mixtures.

Target organ effect/Single exposure: Classification not possible

For mixtures, hazard category was identified based on the classification criteria for mixtures.

Target organ effect/Multi exposure: Classification not possible

For mixtures, hazard category was identified based on the classification criteria for mixtures.

Respiratory toxic: No Classification

For mixtures, hazard category was identified based on the classification criteria for mixtures.

Other information: No information for mixtures.

Ingredient
Base Oil(s)



ENEOS USA Inc.
[E'-ne-ohs]

SAFETY DATA SHEET

SDS: A4308-E231US+

Date Prepared: 2023/03/27

Date Revised:

Product Name: ENEOS X PRIME ENGINE OIL 0W-8

Acute toxicity (oral):	No Classification LC50: > 5000 mg/kg[rat]
Acute toxicity (dermal):	No Classification LC50: > 5000 mg/kg[rat]
Acute toxicity (inhalation):	Exempt classification (Gas) Exempt classification (Vapor) No Classification (Dust/Mist) LC50: > 5 mg/L[rat]
Skin corrosion/irritation:	No Classification
Serious eye damage/irritation:	No Classification Practically None
Respiratory sensitization:	Classification not possible
Skin sensitization:	No Classification None Buehler method [guinea pig]
Mutagenicity:	No Classification Ames Test: Negative
Carcinogenicity:	No Classification EU: Category 2 : R45 need not apply. (NOTE L is Applicable), IARC:3
Reproductive toxicity:	No Classification
Target organ effect/Single exposure:	No Classification
Target organ effect/Multi exposure:	No Classification
Respiratory toxic:	No Classification
Oleoyl sarcosine	
Acute toxicity (oral):	Effect on animals: No relevant information found
Acute toxicity (dermal):	Effect on animals: No relevant information found
Acute toxicity (inhalation):	(Dust/Mist) LC50: 1.37 mg/L[rat]
Skin corrosion/irritation:	Effect on animals: No relevant information found
Serious eye damage/irritation:	Effect on animals: No relevant information found
Respiratory sensitization:	Effect on person: No relevant information found
Skin sensitization:	Effect on animals: No relevant information found
Mutagenicity:	No relevant information found
Carcinogenicity:	No relevant information found
Reproductive toxicity:	No relevant information found
Respiratory toxic:	Effect on person: No relevant information found



ENEOS USA Inc.
[E'-ne-ohs]

SAFETY DATA SHEET

SDS: A4308-E231US+

Date Prepared: 2023/03/27

Date Revised:

Product Name: ENEOS X PRIME ENGINE OIL 0W-8

12. Ecological information

Product

Ecotoxicity

Acute toxicity:	Category 3
Fish acute toxicity:	For mixtures, hazard category was identified based on the classification criteria for mixtures.
Daphnia acute toxicity:	No information.
Algae acute toxicity:	For mixtures, hazard category was identified based on the classification criteria for mixtures.
Chronic toxicity:	No Classification
Fish chronic toxicity:	For mixtures, hazard category was identified based on the classification criteria for mixtures.
Daphnia chronic toxicity:	No information.
Algae chronic toxicity:	For mixtures, hazard category was identified based on the classification criteria for mixtures.
Persistence and degradability :	No information available on mixtures
Bioaccumulative potential :	No information for mixtures.
Mobility in soil:	No information for mixtures.
Dangerous for the ozone layer:	Classification not possible
Other impact :	No information for mixtures.

Ingredient

Base Oil(s)

Ecotoxicity

Acute toxicity:	No Classification
Fish acute toxicity:	96hLC50: > 5000 mg/L[Oncorhynchus mykiss]
Daphnia acute toxicity:	48hEC50: > 1000 mg/L[Daphnia magna]
Chronic toxicity:	No Classification
Dangerous for the ozone layer:	Classification not possible



ENEOS USA Inc.
[E'-ne-ohs]

SAFETY DATA SHEET

SDS: A4308-E231US+

Date Prepared: 2023/03/27

Date Revised:

Product Name: ENEOS X PRIME ENGINE OIL 0W-8

13. Disposal considerations

Disposal methods: Dispose of contents/container in accordance with local/regional/national/international regulations.

Every customer/user of the product should dispose of industrial waste on its own responsibility, otherwise it must rely on a company authorized by prefectural governor for treating industrial waste or a local public body involved in the disposal of industrial waste for proper disposal.

Before disposal of used container, remove contents completely.

14. Transport information

IATA	UN classification:	Not regulated
	UN number:	Not regulated
	Proper shipping name:	Not regulated
	Packing group:	Not regulated
IMDG	UN classification:	Not regulated
	UN number:	Not regulated
	Proper shipping name:	Not regulated
	Packing group:	Not regulated
Domestic restriction:		No information.
Specific security precaution and condition of transportation:		Transport containers without causing any significant friction or shaking.

15. Regulatory information

US California Proposition 65

This product can expose you to chemicals including:



ENEOS USA Inc.
[E'-ne-ohs]

SAFETY DATA SHEET

SDS: A4308-E231US+

Date Prepared: 2023/03/27

Date Revised:

Product Name: ENEOS X PRIME ENGINE OIL 0W-8

Ethylene Glycol 26(ppm)

Superfund Amendments and Reauthorization Act of 1986 (SARA Title III)

None present or none present in regulated concentrations.

Australia(AICS) :	All components are listed or exempted.
Canada(DSL) :	All components are listed or exempted.
China(IECSC) :	One or more components are not listed.
EU(REACH) :	In the case where one or more components are not listed or, even if listed, in the case of importing to the country or area concerned, an application or notification is required.
Korea(K-REACH) :	In the case where one or more components are not listed or, even if listed, in the case of importing to the country or area concerned, an application or notification is required.
New Zealand(NZIoC) :	One or more components are not listed.
Philippines(PICCS) :	All components are listed or exempted.
Taiwan(TCSI) :	All components are listed or exempted.
USA(TSCA) :	All components are listed or exempted.

16. Other information

NFPA	Health hazard rating blue:0, Flammability hazard rating:1
HMIS	Health Ratings:0, Flammability Ratings:1
Date Prepared :	2023/03/27
Reference	No information.
Disclaimer:	We at ENEOS Corporation have prepared the copyrighted Safety Data Sheet to provide reference information on the hazardous chemical product of interest for our customers/users to ensure secure and safe handling. We would like every customer/user of the product to refer to the information and understand the necessity of taking appropriate measures for the actual handling conditions on their own responsibilities for optimum practical application of the product of interest. Consequently, the Safety Data Sheet is not intended to guarantee the safety of the product referenced to herein.