

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SDS ID: 31567

Issue date: 3/18/2024 Version: 1.0

SECTION 1: Identification

1 1 Identification

Product form : Mixture

Product name : Mighty Brightline Clear Coat Protectant

1.2. Recommended use and restrictions on use

No additional information available

1.3. Supplier

Mighty Auto Parts 650 Engineering Drive Peachtree Corners, GA 30092 USA T 800-829-3900

1.4. Emergency telephone number

Emergency number : 1-800-424-9300 (CHEMTREC)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids Category 4 H227 Combustible liquid

Serious eye damage/eye irritation Category 2 H319 Causes serious eye irritation

Full text of H statements: see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)



Signal word (GHS US) : Warning

Hazard statements (GHS US) : H227 - Combustible liquid

H319 - Causes serious eye irritation

Precautionary statements (GHS US) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P264 - Wash hands, forearms and face thoroughly after handling.

 ${\tt P280-Wear\ protective\ gloves/protective\ clothing/eye\ protection/face\ protection}.$

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P337+P313 - If eye irritation persists: Get medical advice/attention.

P370+P378 - In case of fire: Use media other than water to extinguish.

P403+P235 - Store in a well-ventilated place. Keep cool.

P501 - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation.

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
HYDROTREATED MIDDLE DISTILLATE (PETROLEUM)	CAS-No.: 64742-46-7	15 – 25	Asp. Tox. 1, H304
PROPAN-2-OL	CAS-No.: 67-63-0	1 – 10	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
2-BUTOXYETHANOL	CAS-No.: 111-76-2	1 – 5	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319
NONYLPHENOL POLYETHYLENE GLYCOL ETHER	CAS-No.: 127087-87- 0	1 – 5	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Acute Tox. 3 (Inhalation:dust,mist), H331 Skin Irrit. 2, H315 Eye Dam. 1, H318

^{*}Chemical name. CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : If you feel unwell, seek medical advice.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : Although no appropriate human or animal health effects data are known to exist, this material is

expected to be an inhalation hazard.

Symptoms/effects after skin contact : None under normal conditions.

Symptoms/effects after eye contact : Eye irritation.

Symptoms/effects after ingestion : None under normal conditions.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

3/18/2024 (Issue date) US - en 2/12

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard : Combustible liquid.

Explosion hazard : No direct explosion hazard. Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper

protective equipment, including respiratory protection.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb

spillage to prevent material-damage.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and

eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer

to section 8: "Exposure controls/personal protection".

Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent

migration and entry into sewers or streams. Stop leak, if possible without risk.

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public

waters

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

3/18/2024 (Issue date) US - en 3/12

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking. Wear personal protective equipment. Avoid

contact with skin and eyes.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the

product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep in a cool, well-ventilated place away from heat.

Storage conditions : Store in a well-ventilated place. Keep cool.

Packaging materials : Store always product in container of same material as original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

PROPAN-2-OL (67-63-0)		
USA - ACGIH - Occupational Exposure Limits		
Local name	2-Propanol	
ACGIH OEL TWA	200 ppm	
ACGIH OEL STEL	400 ppm	
Remark (ACGIH)	TLV® Basis: Eye & URT irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI	
Regulatory reference	ACGIH 2022	
USA - ACGIH - Biological Exposure Indices		
Local name	2-PROPANOL	
BEI (BLV)	40 mg/l Parameter: Acetone - Medium: urine - Sampling time: End of shift at end of workweek - Notations: B, Ns	
Regulatory reference	ACGIH 2022	
USA - OSHA - Occupational Exposure Limits		
Local name	Isopropyl alcohol	
OSHA PEL TWA	980 mg/m³	
	400 ppm	
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1	

2-BUTOXYETHANOL (111-76-2)

USA - ACGIH - Occupational Exposure Limits		
Local name	2-Butoxyethanol (EGBE)	
ACGIH OEL TWA	20 ppm	
Remark (ACGIH)	TLV® Basis: Eye & URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI	
Regulatory reference	ACGIH 2023	
USA - ACGIH - Biological Exposure Indices		
Local name	2- BUTOXYETHANOL	

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2-BUTOXYETHANOL (111-76-2)		
BEI (BLV)	200 mg/g Kreatinin Parameter: Butoxyacetic acid (BAA) (with hydrolysis) - Medium: urine - Sampling time: End of shift	
Regulatory reference	ACGIH 2023	
USA - OSHA - Occupational Exposure Limits		
Local name	2-Butoxyethanol	
OSHA PEL TWA 240 mg/m³		
	50 ppm	
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1	

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):







SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Color : red
Odor : Fruity

Odor threshold : No data available

pH : 7.1

Melting point : Not applicable
Freezing point : No data available
Boiling point : > 100 °C

Flash point : 80 °C

Relative evaporation rate (butyl acetate=1) : No data available

3/18/2024 (Issue date) US - en 5/12

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Flammability (solid, gas) : Not applicable.

Vapor pressure : No data available

Relative vapor density at 20°C : No data available

Relative density : 0.95

Solubility soluble in water. Partition coefficient n-octanol/water (Log Pow) : No data available No data available Auto-ignition temperature Decomposition temperature No data available Viscosity, kinematic No data available Viscosity, dynamic No data available : No data available **Explosion limits** Explosive properties : No data available Oxidizing properties : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified Acute toxicity (dermal) : Not classified Acute toxicity (inhalation) : Not classified

PROPAN-2-OL (67-63-0)	
LD50 dermal rabbit	16400 ml/kg (Equivalent or similar to OECD 402, 24 h, Rabbit, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat [ppm]	> 10000 ppm (Equivalent or similar to OECD 403, 6 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))
ATE US (oral)	5840 mg/kg body weight

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

According to Federal Register / Vol. 77, No. 58 / Mo	onday, march 26, 2012 / Rules and Regulations
PROPAN-2-OL (67-63-0)	
ATE US (dermal)	12890400 mg/kg body weight
2-BUTOXYETHANOL (111-76-2)	
LD50 oral	1414 mg/kg body weight Animal: guinea pig, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 1020 - 1961
LD50 dermal rat	> 2000 mg/kg Source: ECHA
ATE US (oral)	1414 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h
NONYLPHENOL POLYETHYLENE GI	LYCOL ETHER (127087-87-0)
LD50 oral	657 mg/kg body weight (Rabbit, Male / female, Experimental value, Oral)
LC50 Inhalation - Rat (Dust/Mist)	0.52 – 1.03 mg/l
ATE US (oral)	657 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	0.52 mg/l/4h
Skin corrosion/irritation	: Not classified pH: 7.1
PROPAN-2-OL (67-63-0)	pm. 7.1
рН	No data available in the literature
NONYLPHENOL POLYETHYLENE GI	LYCOL ETHER (127087-87-0)
рН	5 – 7 (20 g/l)
Serious eye damage/irritation	: Causes serious eye irritation.
BBOBAN O OL (OZ OO O)	pH: 7.1
PROPAN-2-OL (67-63-0)	
pH	No data available in the literature
NONYLPHENOL POLYETHYLENE GI	
pH	5 – 7 (20 g/l)
Respiratory or skin sensitization Germ cell mutagenicity	: Not classified : Not classified
Carcinogenicity	: Not classified
PROPAN-2-OL (67-63-0)	
IARC group	3 - Not classifiable
2-BUTOXYETHANOL (111-76-2)	
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified

3/18/2024 (Issue date) US - en 7/12

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
2-BUTOXYETHANOL (111-76-2)	
NOAEL (dermal,rat/rabbit,90 days)	> 150 mg/kg body weight Animal: rabbit, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)
Aspiration hazard	: Not classified
/iscosity, kinematic	: No data available
PROPAN-2-OL (67-63-0)	
Viscosity, kinematic	No data available in the literature
NONYLPHENOL POLYETHYLENE GI	YCOL ETHER (127087-87-0)
Viscosity, kinematic	Not determined
Symptoms/effects after inhalation	: Although no appropriate human or animal health effects data are known to exist, this material i expected to be an inhalation hazard.
Symptoms/effects after skin contact	: None under normal conditions.
Symptoms/effects after eye contact	: Eye irritation.
Symptoms/effects after ingestion	: None under normal conditions.

SECTION 12: Ecological information

12.1. Toxicity	
Ecology - general	 The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.
PROPAN-2-OL (67-63-0)	
LC50 - Fish [1]	9640 – 10000 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Lethal)
2-BUTOXYETHANOL (111-76-2)	
LC50 - Fish [1]	1474 mg/l Source: ECHA
EC50 - Crustacea [1]	1800 mg/l Source: ECHA
EC50 72h - Algae [1]	911 mg/l Source: ECHA
NOEC (chronic)	100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	≥ 100 mg/l Test organisms (species): Oryzias latipes Duration: '14 d'
NONYLPHENOL POLYETHYLEN	IE GLYCOL ETHER (127087-87-0)
LC50 - Fish [1]	11.6 mg/l (48 h, Oryzias latipes, Static system, Fresh water, Experimental value)
EC50 - Crustacea [1]	14 mg/l (48 h, Daphnia magna, Static renewal, Fresh water, Experimental value)
EC50 72h - Algae [1]	1948545 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 96h - Algae [1]	12 mg/l (Selenastrum capricornutum, Static system, Fresh water, Experimental value, Nominal concentration)

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.2. Persistence and degradability

,			
Mighty Brightline Clear Coat Protectant			
Persistence and degradability	Not rapidly degradable		
HYDROTREATED MIDDLE DISTILLATE (PETROLEUM) (64742-46-7)			
Persistence and degradability	Not rapidly degradable		
PROPAN-2-OL (67-63-0)			
Persistence and degradability	Biodegradable in the soil, Biodegradable in the soil under anaerobic conditions, Readily biodegradable in water.		
Biochemical oxygen demand (BOD)	1.19 g O₂/g substance		
Chemical oxygen demand (COD)	2.23 g O₂/g substance		
ThOD	2.4 g O ₂ /g substance		
2-BUTOXYETHANOL (111-76-2)			
Persistence and degradability	Not rapidly degradable		
NONYLPHENOL POLYETHYLENE GLYCOL ETHER (127087-87-0)			
Persistence and degradability	Not readily biodegradable in water.		
12.3. Bioaccumulative potential			
PROPAN-2-OL (67-63-0)			
Partition coefficient n-octanol/water (Log Pow)	0.05 (Weight of evidence approach, 25 °C)		

Bioaccumulative potential 2-BUTOXYETHANOL (111-76-2)

Partition coefficient n-octanol/water (Log Pow) 0.81 Source: ECHA

NONYLPHENOL POLYETHYLENE GLYCOL ETHER (127087-87-0)		
BCF - Fish [1]	15 – 53 (Calculated value)	
Partition coefficient n-octanol/water (Log Pow)	5.67 (Practical experience/observation, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).	

Low potential for bioaccumulation (Log Kow < 4).

12.4. Mobility in soil

PROPAN-2-OL (67-63-0)	
Surface tension	No data available (test not performed)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.185 – 0.541 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.

NONYLPHENOL POLYETHYLENE GLYCOL ETHER (127087-87-0)			
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.631 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value)		
Ecology - soil	No (test)data on mobility of the substance available.		

3/18/2024 (Issue date) US - en 9/12

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional waste regulation : Disposal must be done according to official regulations.

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Sewage disposal recommendations : Disposal must be done according to official regulations. Product/Packaging disposal recommendations : Disposal must be done according to official regulations.

Additional information : Do not re-use empty containers.

SECTION 14: Transport information

In accordance with DOT

14.1. UN number

Not regulated for transport

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Not regulated

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : Not regulated

14.4. Packing group

Packing group (DOT) : Not regulated

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

DOT

Not regulated

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

Commercial status of components according to the United States Environmental Protection Agency's Toxic Substances Control Act (TSCA):

Name	CAS-No.	J	Commercial status	Flags
HYDROTREATED MIDDLE DISTILLATE (PETROLEUM)	64742-46-7	Present	Active	
PROPAN-2-OL	67-63-0	Present	Active	

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	CAS-No.	3	Commercial status	Flags
2-BUTOXYETHANOL	111-76-2	Not present	-	
NONYLPHENOL POLYETHYLENE GLYCOL ETHER	127087-87-0	Present	Active	XU

PROPAN-2-OL (67-63-0)

Subject to reporting requirements of United States SARA Section 313

15.2. International regulations

CANADA

HYDROTREATED MIDDLE DISTILLATE (PETROLEUM) (64742-46-7)

Listed on the Canadian DSL (Domestic Substances List)

PROPAN-2-OL (67-63-0)

Listed on the Canadian DSL (Domestic Substances List)

NONYLPHENOL POLYETHYLENE GLYCOL ETHER (127087-87-0)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

HYDROTREATED MIDDLE DISTILLATE (PETROLEUM) (64742-46-7)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

PROPAN-2-OL (67-63-0)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. US State regulations

No additional information available

SECTION 16: Other information

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases	
H225	Highly flammable liquid and vapor
H227	Combustible liquid
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H318	Causes serious eye damage

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases	
H319	Causes serious eye irritation
H331	Toxic if inhaled
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.