Mighty Aerosol Intake Cleaner

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Issue date: 4/25/2022 Revision date: 1/13/2026 Supersedes: 4/25/2022 Version: 2.0

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture

Trade name : Mighty Aerosol Intake Cleaner

Synonym : 0700286

1.2. Other means of identification

Part numbers : SB300; SB300i

1.3. Recommended use of the chemical and restrictions on use

No additional information available

1.4. Supplier's details

Manufacturer

Gold Eagle Company
4400 South Kildare Avenue
Chicago, USA, Illinois 60632-4372
T 1-773-376-4400
https:/www.goldeagle.com/

1.5. Emergency phone number

Emergency number : INFOTrac: 1-800-535-5053

SECTION 2 Hazard Identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquid, Category 3	H226	Flammable liquid and vapor.
Acute toxicity (inhalation:dust,mist), Category 4	H332	Harmful if inhaled.
Skin corrosion/irritation, Category 2	H315	Causes skin irritation.
Serious eye damage/eye irritation, Category 2	H319	Causes serious eye irritation.

Full text of H statements : see section 16

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US) :

Signal word (GHS US) : Danger

Hazard statements (GHS US) : H226 - Flammable liquid and vapor
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H332 - Harmful if inhaled
Causes eye irritation
Contains gas under pressure; may explode if heated
H229 - Pressurized container; may burst if heated
H222 - Extremely flammable aerosol
H280 - Contains gas under pressure; may explode if heated

Precautionary statements (GHS US) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P261 - Avoid breathing dust, fume, gas, mist, vapors, spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves, protective clothing, eye protection, face protection, and hearing protection.
P302+P352 - If on skin: Wash with plenty of water.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332+P313 - If skin irritation occurs: Get medical advice or attention.
P337+P313 - If eye irritation persists: Get medical advice or attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use appropriate media to extinguish.
P403+P235 - Store in a well-ventilated place. Keep cool.
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

No additional information available

2.5. Unknown acute toxicity

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Ethylene glycol monobutyl ether	CAS-No.: 111-76-2	15 – 40	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319
Xylene	CAS-No.: 1330-20-7	15 – 40	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315
Proprietary addtiive	-	7 – 13	Not classified
Triethanolamine	CAS-No.: 102-71-6	7 – 13	Not classified

Name	Product identifier	%	GHS US classification
Propane	CAS-No.: 74-98-6	7 – 13	Flam. Gas 1, H220
Proprietary	-	3 – 7	Not classified

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret
Full text of hazard classes and H-statements : see section 16

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general : Call a poison center/doctor/physician if you feel unwell.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor/physician if you feel unwell.
First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.
Personal protection for first-aid responders. : First-aiders should consider self-protection and use the recommended personal protective equipment (see section 8).

4.2. Most important symptoms/effects, acute and delayed

Potential Adverse human health effects and symptoms : Causes serious eye irritation. Causes severe skin burns. Causes serious eye damage. Causes damage to organs if swallowed. May be fatal if swallowed and enters airways.
Symptoms/effects after inhalation : Harmful if inhaled.
Symptoms/effects after skin contact : Irritation.
Symptoms/effects after eye contact : Eye irritation.
Symptoms/effects after ingestion : None under normal conditions.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment : Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard : Flammable liquid and vapor.
Explosion hazard : No direct explosion hazard.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material-damage.

For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

Environmental precautions : Avoid release to the environment.

6.2. Methods and materials for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk.

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

For further information refer to section 13.

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

Additional hazards when processed : Flammable vapors may accumulate in the container.

7.2. Conditions for safe storage, including incompatibilities

Technical measures : Store in a well-ventilated place. Keep container tightly closed. Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed.

Storage area : Keep only in the original container. Store in a cool area. Store in a well-ventilated place.

Incompatible products : Oxidizing agent. Strong acids. Strong bases.

Incompatible materials : Sources of ignition. Heat sources. Direct sunlight.

Packaging materials : Always store product in container of same material as original container.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Ethylene glycol monobutyl ether (111-76-2)	
USA - ACGIH® - Threshold Limit Values	
Local name	2-Butoxyethanol (EGBE)
ACGIH® TLV® TWA	20 ppm
Remark (ACGIH®)	TLV® Basis: Eye & URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
Regulatory reference	ACGIH 2019
USA - OSHA - Occupational Exposure Limits	
Local name	2-Butoxyethanol
OSHA PEL TWA	240 mg/m³
	50 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

Xylene (1330-20-7)	
USA - OSHA - Occupational Exposure Limits	
Local name	Xylenes (o-, m-, p-isomers)
OSHA PEL TWA	435 mg/m³
	100 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Personal protective equipment:
Gloves. In case of splash hazard: safety glasses. Safety glasses. Wear recommended personal protective equipment.

Hand protection:
Protective gloves

Eye protection:
Safety glasses

Skin and body protection:
Wear suitable protective clothing

Respiratory protection:
[In case of inadequate ventilation] wear respiratory protection.

Personal protective equipment symbol(s):

SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	:	Liquid
Appearance	:	Liquid.
Color	:	Amber to brown
Odor	:	Amine-like
Odor threshold	:	No data available
pH	:	No data available
Melting point	:	Not applicable
Freezing point	:	No data available
Boiling point	:	No data available
Flash point	:	No data available
Flammability (solid, gas)	:	Not applicable.
Vapor pressure	:	No data available
Relative vapor density at 20°C	:	No data available
Relative density	:	≈ 0.9
Density	:	≈ 7.5 lb/gal
Solubility	:	Poorly soluble in water.
Partition coefficient n-octanol/water (Log Pow)	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity, kinematic	:	≈ 3 mm²/s
Explosion limits	:	No data available
Explosive properties	:	No data available.
Oxidizing properties	:	No data available.
Particle characteristics	:	No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

VOC content	:	≈ 100 %

SECTION 10 Stability and reactivity

10.1. Reactivity

Flammable liquid and vapor.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11 Toxicological information

Likely routes of exposure : Dermal. Inhalation. Skin and eye contact.

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Inhalation:dust,mist: Harmful if inhaled.

Mighty Aerosol Intake Cleaner	
ATE US (dust, mist)	1.875 mg/l/4h

Ethylene glycol monobutyl ether (111-76-2)	
LD50 oral rat	1746 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral)
LD50 oral	1414 mg/kg body weight (OECD 401: Acute Oral Toxicity, Guinea pig, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, Rat, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat [ppm]	450 ppm (Equivalent or similar to OECD 403, 4 h, Rat, Female, Experimental value, Inhalation (vapours))
ATE US (oral)	1414 mg/kg body weight
ATE US (gases)	450 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

Xylene (1330-20-7)	
LD50 oral rat	3523 mg/kg body weight (Equivalent or similar to EU Method B.1: Acute Toxicity (Oral), Rat, Male, Experimental value, Oral, 14 day(s))
ATE US (oral)	3523 mg/kg body weight
ATE US (dermal)	1100 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.

Triethanolamine (102-71-6)	
pH	10.5

Serious eye damage/irritation : Causes serious eye irritation.

Triethanolamine (102-71-6)	
pH	10.5

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

Ethylene glycol monobutyl ether (111-76-2)	
IARC group	3 - Not classifiable

Xylene (1330-20-7)	
IARC group	3 - Not classifiable

Triethanolamine (102-71-6)	
IARC group	3 - Not classifiable

Reproductive toxicity : Not classified
STOT-single exposure : Not classified
STOT-repeated exposure : Not classified
Aspiration hazard : Not classified

Mighty Aerosol Intake Cleaner	
Viscosity, kinematic	≈ 3 mm²/s

Ethylene glycol monobutyl ether (111-76-2)	
Viscosity, kinematic	3.49 mm²/s (25 °C)

Xylene (1330-20-7)	
Viscosity, kinematic	0.74 mm²/s (20 °C)

Triethanolamine (102-71-6)	
Viscosity, kinematic	525.26

Potential Adverse human health effects and symptoms : Causes serious eye irritation. Causes severe skin burns. Causes serious eye damage. Causes damage to organs if swallowed. May be fatal if swallowed and enters airways.
Symptoms/effects after inhalation : Harmful if inhaled.
Symptoms/effects after skin contact : Irritation.
Symptoms/effects after eye contact : Eye irritation.
Symptoms/effects after ingestion : None under normal conditions.

SECTION 12 Ecological information

12.1. Ecotoxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short–term (acute) : Not classified
Hazardous to the aquatic environment, long–term (chronic) : Not classified

Ethylene glycol monobutyl ether (111-76-2)	
LC50 - Fish [1]	1474 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 - Crustacea [1]	1550 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 72h - Algae [1]	911 mg/l (OECD 201: Alga, Growth Inhibition Test, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)

Xylene (1330-20-7)	
LC50 - Fish [1]	2.6 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static renewal, Fresh water, Read-across, Lethal)
ErC50 algae	4.36 mg/l (OECD 201: Alga, Growth Inhibition Test, 73 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)

12.2. Persistence and degradability

Mighty Aerosol Intake Cleaner	
Persistence and degradability	Not rapidly degradable

Ethylene glycol monobutyl ether (111-76-2)	
Persistence and degradability	Readily biodegradable in water.

Proprietary	
Persistence and degradability	Not rapidly degradable

Proprietary addtiive	
Persistence and degradability	Not rapidly degradable

Xylene (1330-20-7)	
Persistence and degradability	Biodegradable in the soil, Readily biodegradable in water.

Triethanolamine (102-71-6)	
Persistence and degradability	Not rapidly degradable

Propane (74-98-6)	
Persistence and degradability	Not rapidly degradable

12.3. Bioaccumulative potential

Ethylene glycol monobutyl ether (111-76-2)	
Partition coefficient n-octanol/water (Log Pow)	0.81 (Test data, 20 °C)
Partition coefficient n-octanol/water (Log Kow)	0.83
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

Xylene (1330-20-7)	
BCF - Fish [1]	7.2 – 25.9 (56 day(s), Oncorhynchus mykiss, Flow-through system, Fresh water, Read-across)
Partition coefficient n-octanol/water (Log Pow)	3.2 (Read-across, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

Triethanolamine (102-71-6)	
Partition coefficient n-octanol/water (Log Kow)	-1

Propane (74-98-6)	
Partition coefficient n-octanol/water (Log Kow)	2.36

12.4. Mobility in soil

Ethylene glycol monobutyl ether (111-76-2)	
Surface tension	65.03 mN/m (20 °C, 2 g/l)
Ecology - soil	Low potential for adsorption in soil.

Xylene (1330-20-7)	
Surface tension	28.01 – 29.76 mN/m (25 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.73 (log Koc, Equivalent or similar to OECD 121, Read-across)

Xylene (1330-20-7)	
Ecology - soil	Low potential for adsorption in soil. May be harmful to plant growth, blooming and fruit formation.

12.5. Other adverse effects

Ozone : Not classified
Fluorinated greenhouse gases : No

SECTION 13 Disposal considerations

Regional waste regulation : Disposal must be done according to official regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations : Disposal must be done according to official regulations.
Product/Packaging disposal recommendations : Remove waste in accordance with local and/or national regulations. Disposal must be done according to official regulations.
Additional information : Flammable vapors may accumulate in the container. Do not re-use empty containers.
Ecological waste information : The waste of the product should be considered as hazardous as the product itself, with the likelihood of impacting the environment in the same way. Consider the handling and disposal of the waste as defined by the product itself.

SECTION 14 Transport information

In accordance with DOT / IMDG

14.1. UN number

UN-No. (DOT) : UN1950
UN-No. (IMDG) : 1950

14.2. UN Proper Shipping Name

Proper Shipping Name (DOT) : Aerosols
Proper Shipping Name (IMDG) : AEROSOLS

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : 2.1
Hazard labels (DOT) : 2.1

IMDG

Transport hazard class(es) (IMDG) : 2.1
Hazard labels (IMDG) : 2.1

14.4. Packing group

Packing group (DOT) : Not applicable
Packing group (IMDG) : Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

DOT

UN-No. (DOT) : UN1950
DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.
DOT Packaging Exceptions (49 CFR 173.xxx) : 306
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 75 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg
DOT Vessel Stowage Location : A - The material may be stowed ‘‘on deck’’ or ‘‘under deck’’ on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other : 25 - Protected from sources of heat,87 - Stow ‘‘separated from’’ Class 1 (explosives) except Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

IMDG

Special provision (IMDG) : 63, 190, 277, 327, 344, 381, 959
Limited quantities (IMDG) : SP277
Excepted quantities (IMDG) : E0
Packing instructions (IMDG) : P207, LP200
Packing provisions (IMDG) : PP87, L2
EmS-No. (Fire) : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES
EmS-No. (Spillage) : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)
Stowage category (IMDG) : None
Stowage and handling (IMDG) : SW1, SW22
Segregation (IMDG) : SG69

SECTION 15 Regulatory information

15.1. Federal regulations

Mighty Aerosol Intake Cleaner

Subject to reporting requirements of United States SARA Section 313

Commercial status of components according to the United States Environmental Protection Agency’s Toxic Substances Control Act (TSCA):

Name	CAS-No.	Listing	Commercial status	Flags
Ethylene glycol monobutyl ether	111-76-2	Present	Active	
Proprietary		Not present	-	
Proprietary addtiive		Not present	-	
Xylene	1330-20-7	Present	Active	
Triethanolamine	102-71-6	Present	Active	
Propane	74-98-6	Not present	-	

Xylene (1330-20-7)	
Subject to reporting requirements of United States SARA Section 313 Listed on EPA Hazardous Air Pollutant (HAPS)	
CERCLA RQ	100 lb

15.2. International regulations

CANADA

Ethylene glycol monobutyl ether (111-76-2)
Listed on the Canadian DSL (Domestic Substances List)

Xylene (1330-20-7)
Listed on the Canadian DSL (Domestic Substances List)

Triethanolamine (102-71-6)
Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

Xylene (1330-20-7)
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Triethanolamine (102-71-6)
Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. State regulations

No additional information available

SECTION 16 Other information

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)
Revision date : 1/13/2026
Issue date : 4/25/2022

Full text of hazard classes and H-statements	
H220	Extremely flammable gas
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H302	Harmful if swallowed
H312	Harmful in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled

NFPA health hazard	:	3 - Materials that, under emergency conditions, can cause serious or permanent injury.
NFPA fire hazard	:	3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.
NFPA reactivity	:	2 - Materials that readily undergo violent chemical change at elevated temperatures and pressures.



Hazard Rating

Health	:	3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given
Flammability	:	3 Serious Hazard - Materials capable of ignition under almost all normal temperature conditions. Includes flammable liquids with flash points below 73 F and boiling points above 100 F. as well as liquids with flash points between 73 F and 100 F. (Classes IB & IC)
Physical	:	2 Moderate Hazard - Materials that are unstable and may undergo violent chemical changes at normal temperature and pressure with low risk for explosion. Materials may react violently with water or form peroxides upon exposure to air.
Personal protection	:	C - Safety glasses, Gloves, Synthetic apron

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.