



# Windshield Repair Kit – Resin 1

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Issue date: 2023-12-12  
Revision date: 2023-12-12  
Version: 1.0

## SECTION 1: Identification

### 1.1. Identification

Product form : Mixture  
Product name : Windshield Repair Kit - Resin 1

### 1.2. Recommended use and restrictions on use

Recommended use : UV-curable liquid adhesive used to fill in windshield damage.

### 1.3. Supplier

**Supplier**  
SRP Products Inc  
650 Pelham Blvd, Suite 100  
St. Paul, MN 55114 - USA  
T 800-548-6872  
[www.srpproducts.com](http://www.srpproducts.com)

**Distributor**  
FIX AUTO  
99 Émilien-Marcoux Suite 101  
Blainville, Québec J7C 0B4 - Canada  
T (450) 433-1414

### 1.4. Emergency telephone number

Emergency number : (800) 420-8036 (ProPharma, 24-hr)

## SECTION 2: Hazard(s) identification

### 2.1. Classification of the substance or mixture

#### GHS classification

Skin Irritation Category 2  
Eye Irritation Category 2A  
Skin Sensitization Category 1  
Specific Target Organ Toxicity (Single Exposure) Category 3 (Respiratory Irritation)

### 2.2. GHS Label elements, including precautionary statements

#### GHS labelling

Hazard pictograms (GHS)



Signal word (GHS) : Warning  
Hazard statements (GHS) : Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
May cause respiratory irritation.  
Precautionary statements (GHS) : If medical advice is needed, have product container or label at hand.  
Keep out of reach of children.  
Read label before use.  
Avoid breathing vapours.  
Wear protective gloves/protective clothing/eye protection/face protection.  
Wash hands, forearms and face thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
Contaminated work clothing must not be allowed out of the workplace.  
If on skin: Wash with plenty of water.  
Take off contaminated clothing and wash it before reuse.

# Windshield Repair Kit – Resin 1

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

If skin irritation or rash occurs: Get medical advice/attention.  
If inhaled: Remove person to fresh air and keep comfortable for breathing.  
Call a poison center or doctor if you feel unwell.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
If eye irritation persists: Get medical advice/attention.  
Store locked up in a well-ventilated place. Keep container tightly closed.  
Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity

Not applicable

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%
2-Propenoic acid, 2-methyl-, phenylmethyl ester	2-Propenoic acid, 2-methyl-, phenylmethyl ester Phenylmethyl 2-methylprop-2-enoate / BENZYL METHACRYLATE / Methacrylic acid, benzyl ester / Benzyl methacrylate	CAS-No.: 2495-37-6	30 – 60
2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol	2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol Monoester of methacrylic acid and propane-1,2-diol / hydroxypropyl methacrylate / HYDROXYPROPYL METHACRYLATE / Propylene glycol monomethacrylate / Hydroxypropyl methacrylate / Methacrylic acid, monoester with propane-1,2-diol / Methacrylic acid, monoester with 1,2-propanediol	CAS-No.: 27813-02-1	20 - 40
2-Hydroxyethyl methacrylate	2-Hydroxyethyl methacrylate Methacrylic acid, monoester with ethylene glycol / 2-Hydroxyethyl 2-methylprop-2-enoate / Ethylene glycol monomethacrylate / HEMA / Ethylene glycol methacryl ether / Hydroxyethyl methacrylate / 2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester / Monomer MG-1 / Methacrylic acid, 2-hydroxyethyl ester / Ethylene glycol methacrylate	CAS-No.: 868-77-9	0.5 - 1.5

\*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures after inhalation

: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

# Windshield Repair Kit – Resin 1

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

First-aid measures after skin contact	: IF ON SKIN: Wash with plenty of Water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation	: May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

### 4.3. Immediate medical attention and special treatment, if necessary

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Carbon dioxide (CO <sub>2</sub> ). Dry chemical
Unsuitable extinguishing media	: Do not use water jet.

### 5.2. Specific hazards arising from the chemical

Fire hazard	: Products of combustion may include, and are not limited to: oxides of carbon. Hydrocarbons. Nitrogen oxides. Irritating vapours.
-------------	--

### 5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting	: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).
--------------------------------	--

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.
------------------	--

#### 6.1.1. For non-emergency personnel

No additional information available

#### 6.1.2. For emergency responders

No additional information available

### 6.2. Environmental precautions

Prevent entry to sewers and public waters.

### 6.3. Methods and material for containment and cleaning up

For containment	: Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.
-----------------	---

# Windshield Repair Kit – Resin 1

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Provide ventilation.

### 6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection".

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Read label before use. Avoid contact with skin and eyes. Avoid breathing vapours. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Wear appropriate PPE (see Section 8).

Hygiene measures : Wash hands, forearms and face thoroughly after handling. Take off contaminated clothing and wash it before reuse. Contaminated work clothing should not be allowed out of the workplace.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep out of the reach of children. Keep container tightly closed. Store in a dry, cool and well-ventilated place.

Incompatible materials : Refer to Section 10 on Incompatible Materials.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Windshield Repair Kit - Resin 1

No additional information available

#### 2-Propenoic acid, 2-methyl-, phenylmethyl ester (2495-37-6)

No additional information available

#### 2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)

No additional information available

#### 2-Hydroxyethyl methacrylate (868-77-9)

No additional information available

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station. Provide readily accessible eye wash stations and safety showers.

Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

#### Hand protection:

Wear suitable gloves resistant to chemical penetration. Consult glove manufacturer's product information on material suitability and material thickness.

#### Eye protection:

Wear eye/face protection

#### Skin and body protection:

Wear suitable protective clothing

# Windshield Repair Kit – Resin 1

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. SDSs cannot provide detailed and complete respiratory protection guidelines. Selection of respiratory protection must be done by a qualified person who has assessed the work environment.

### Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear.
Colour	: Clear
Odour	: Acrylic
Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Flammability	: Not flammable.
Vapour pressure	: No data available
Relative vapour density at 20°C / 68 °F	: No data available
Relative density	: 1.06
Solubility	: No data available.
Partition coefficient n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 18 mm <sup>2</sup> /s @ 22°C (72°F)
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No dangerous reactions known under normal conditions of use.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

# Windshield Repair Kit – Resin 1

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

### 10.4. Conditions to avoid

Heat. Incompatible materials.

### 10.5. Incompatible materials

Strong oxidizers.

### 10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon. Hydrocarbons. Nitrogen oxides. Irritating vapours.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified.
Acute toxicity (dermal)	: Not classified.
Acute toxicity (inhalation)	: Not classified.

#### 2-Propenoic acid, 2-methyl-, phenylmethyl ester (2495-37-6)

LD50 dermal rat	> 2000 mg/kg
-----------------	--------------

#### 2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)

LD50 oral rat	11200 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
ATE CA (oral)	11200 mg/kg bodyweight

#### 2-Hydroxyethyl methacrylate (868-77-9)

LD50 oral rat	5050 mg/kg
LD50 dermal rabbit	> 3000 mg/kg
ATE CA (oral)	5050 mg/kg bodyweight

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified.
Carcinogenicity	: Not classified.
Reproductive toxicity	: Not classified.
STOT-single exposure	: May cause respiratory irritation.

#### 2-Propenoic acid, 2-methyl-, phenylmethyl ester (2495-37-6)

STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified.

#### 2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)

NOAEL (oral, rat, 90 days)	300 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
----------------------------	---

#### 2-Hydroxyethyl methacrylate (868-77-9)

LOAEC (inhalation, rat, gas, 90 days)	350 ppm Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study), Remarks on results: other:
NOAEC (inhalation, rat, gas, 90 days)	100 ppm Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study), Remarks on results: other:

# Windshield Repair Kit – Resin 1

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Aspiration hazard	: Not classified.
<b>Windshield Repair Kit - Resin 1</b>	
Viscosity, kinematic	18 mm <sup>2</sup> /s @ 22°C (72°F)
Symptoms/effects after inhalation	: May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

#### 2-Propenoic acid, 2-methyl-, phenylmethyl ester (2495-37-6)

LC50 - Fish [1]	4.25 – 5.13 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
-----------------	--

#### 2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)

EC50 - Crustacea [1]	> 143 mg/l Test organisms (species): Daphnia magna
NOEC (chronic)	45.2 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

#### 2-Hydroxyethyl methacrylate (868-77-9)

LC50 - Fish [1]	213 – 242 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 - Crustacea [1]	380 mg/l Test organisms (species): Daphnia magna
LC50 - Fish [2]	227 mg/l (Exposure time: 96 h - Species: Pimephales promelas)
LOEC (chronic)	49.6 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	24.1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

### 12.2. Persistence and degradability

#### Windshield Repair Kit - Resin 1

Persistence and degradability	Not established.
-------------------------------	------------------

### 12.3. Bioaccumulative potential

#### Windshield Repair Kit - Resin 1

Bioaccumulative potential	Not established.
---------------------------	------------------

#### 2-Propenoic acid, 2-methyl-, phenylmethyl ester (2495-37-6)

Partition coefficient n-octanol/water	3.1
---------------------------------------	-----

#### 2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)

Partition coefficient n-octanol/water	0.97 (at 20 °C (at pH 2-8)
---------------------------------------	----------------------------

#### 2-Hydroxyethyl methacrylate (868-77-9)

BCF - Fish [1]	1.34 – 1.54
----------------	-------------

# Windshield Repair Kit – Resin 1

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

### 2-Hydroxyethyl methacrylate (868-77-9)

Partition coefficient n-octanol/water	0.42 (at 25 °C (at pH >=5.9-<=6.1))
---------------------------------------	-------------------------------------

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Other information : No other effects known.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

## SECTION 14: Transport information

In accordance with DOT / TDG

### 14.1. UN number

Not regulated for transport

### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Not applicable  
Proper Shipping Name (TDG) : Not applicable

### 14.3. Transport hazard class(es)

#### DOT

Transport hazard class(es) (DOT) : Not applicable

#### TDG

Transport hazard class(es) (TDG) : Not applicable

### 14.4. Packing group

Packing group (DOT) : Not applicable  
Packing group (TDG) : Not applicable

### 14.5. Environmental hazards

Other information : No supplementary information available.

### 14.6. Special precautions for user

Special transport precautions : Do not handle until all safety precautions have been read and understood.

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

# Windshield Repair Kit – Resin 1

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

### SECTION 15: Regulatory information

#### 15.1 Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories except for:

Aromatic Urethane Methacrylate	CAS-No. 2978411-57-1
--------------------------------	----------------------

#### 15.2. International regulations

No additional information available

#### 15.3. US State regulations



**WARNING:** This product can expose you to Methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### SECTION 16: Other information

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Revision date : 12/12/2023

Other information : None.

Prepared by : Nexreg Compliance Inc.  
[www.Nexreg.com](http://www.Nexreg.com)



#### Full text of H-statements

Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

SDS HazCom 2012 - WHMIS 2015 (Nexreg) 2023

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.



# Windshield Repair Kit – Resin 2

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022  
Issue date: 2025-02-19 Revision date: 2025-03-19 Version: 2.0

### SECTION 1 Identification

#### 1.1. Product identifier

Product form : Mixture  
Product name : Windshield Repair Kit – Resin 2

#### 1.2. Other means of identification

No additional information available

#### 1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Windscreen/Windshield repair

#### 1.4. Supplier's details

##### Supplier

SRP Products Inc  
650 Pelham Blvd, Suite 100  
St. Paul, MN, 55114  
USA  
T 001 952-944-8000  
[www.srpproducts.com](http://www.srpproducts.com)

##### Distributor

FIX Auto  
99 Emilien-Marcoux Suite 101  
Blainville, Quebec J7C 0B4,  
Canada  
T (450) 433-1414

#### 1.5. Emergency phone number

Emergency number : (800) 420-8036 (ProPharma, 24-hr)

### SECTION 2 Hazard identification

#### 2.1. Classification of the substance or mixture

##### GHS classification

Skin corrosion/irritation, Category 2  
Serious eye damage/eye irritation, Category 2  
Skin sensitization, Category 1

#### 2.2. Label elements

##### GHS labelling

Hazard pictograms (GHS) :



Signal word (GHS)

: Warning

Hazard statements (GHS)

: Causes skin irritation

May cause an allergic skin reaction

Causes serious eye irritation

Precautionary statements (GHS)

: Avoid breathing dust, fume, gas, mist, vapours, spray.

Wash hands, forearms and face thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves

If on skin: Wash with plenty of water.

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice or attention.

# Windshield Repair Kit – Resin 2

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
If eye irritation persists: Get medical advice or attention.  
Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

### 2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

### 2.4. Hazards not otherwise classified

No additional information available

### 2.5. Unknown acute toxicity

Not applicable

## SECTION 3 Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%Weight
Aliphatic urethane acrylate	Aliphatic urethane acrylate	CAS-No.: 143566-26-1	15 – 40
2-Hydroxyethyl methacrylate	2-Hydroxyethyl methacrylate Ethylene glycol methacryl ether / Methacrylic acid, monoester with ethylene glycol / 2-Hydroxyethyl 2- methylprop-2-enoate / Ethylene glycol monomethacrylate / HEMA / 2-Propenoic acid, 2-methyl-, 2- hydroxyethyl ester / Monomer MG-1 / Methacrylic acid, 2-hydroxyethyl ester / Ethylene glycol methacrylate / Hydroxyethyl methacrylate	CAS-No.: 868-77-9	15 – 40
2-Propenoicacid,(1R,2R,4R)-1,7,7- trimethylbicyclo[2.2.1]hept-2- ylester,rel-	2-Propenoicacid,(1R,2R,4R)-1,7,7- trimethylbicyclo[2.2.1]hept-2- ylester,rel- 2-Propenoic acid, (1R,2R,4R)-1,7,7- trimethylbicyclo[2.2.1]hept-2-yl ester, rel- / exo-1,7,7- Trimethylbicyclo[2.2.1]hept-2-yl acrylate / Acrylic acid, isobornyl ester / Isobornyl acrylate / (1R,2R,4R)-rel-1,7,7- Trimethylbicyclo[2.2.1]heptan-2-yl acrylate / ISOBORNYL ACRYLATE	CAS-No.: 5888-33-5	3 – 7
2-Propenoic acid	2-Propenoic acid Acroleic acid / Propenoic acid / 2- Propenoic acid / Acrylic acid, stabilized / Prop-2-enoic acid / ACRYLIC ACID	CAS-No.: 79-10-7	1 < 3

# Windshield Repair Kit – Resin 2

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Name	Chemical name / Synonyms	Product identifier	%Weight
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate Decanedioic acid, bis(1,2,2,6,6-pentamethyl-4-piperidinyl) ester / Decanedioic acid, 1,10-bis(1,2,2,6,6-pentamethyl-4-piperidinyl) ester / Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate / Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) decanedioate / Bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate / PENTAMETHYL PIPERIDINYL SESQUISEBACATE	CAS-No.: 41556-26-7	0.5 < 5
Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidinyl ester	Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidinyl ester Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate / Decanedioic acid, 1-methyl 10-(1,2,2,6,6-pentamethyl-4-piperidinyl) ester / Methyl 1,2,2,6,6-pentamethylpiperidin-4-yl decanedioate / Methyl (1,2,2,6,6-Pentamethyl-4-Piperidyl)sebacate / methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	CAS-No.: 82919-37-7	0.1 – 1

\*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

## SECTION 4 First-aid measures

### 4.1. Description of necessary first-aid measures

First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.

First-aid measures after skin contact : IF ON SKIN: Wash with plenty of water. Wash clothing before re-using. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

### 4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation : May cause irritation to the respiratory tract.

Symptoms/effects after skin contact : Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

Symptoms/effects after ingestion : May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

### 4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment : Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

# Windshield Repair Kit – Resin 2

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.  
Unsuitable extinguishing media : Do not use water jet.

#### 5.2. Specific hazards arising from the chemical

Fire hazard : Products of combustion may include, and are not limited to: oxides of carbon. Irritating vapours.

#### 5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

### SECTION 6 Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

##### For non-emergency personnel

No additional information available

##### For emergency responders

Environmental precautions : Prevent entry to sewers and public waters.

#### 6.2. Methods and materials for containment and cleaning up

For containment : Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.

Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Provide ventilation.

For further information refer to section 8: "Exposure controls/personal protection"

### SECTION 7 Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Avoid breathing vapour. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Avoid contact with eyes, on skin, or on clothing.  
Hygiene measures : Take off contaminated clothing and wash it before reuse. Wash hands, forearms and face thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.

#### 7.2. Conditions for safe storage, including incompatibilities

Storage conditions : Keep out of the reach of children. Keep container tightly closed. Store in a dry, cool and well-ventilated place.  
Specific end uses : Not available.

# Windshield Repair Kit – Resin 2

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

### SECTION 8 Exposure controls/personal protection

#### 8.1. Control parameters

##### 2-Propenoic acid (79-10-7)

##### USA - ACGIH - Occupational Exposure Limits

ACGIH OEL TWA	2 ppm
ACGIH chemical category	Not Classifiable as a Human Carcinogen, Skin - potential significant contribution to overall exposure by the cutaneous route

##### USA - NIOSH - Occupational Exposure Limits

NIOSH REL TWA	6 mg/m <sup>3</sup>
NIOSH REL TWA	2 ppm
US-NIOSH chemical category	SK: SYS-DIR(COR) Apr 2017

#### 8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station. Provide readily accessible eye wash stations and safety showers.
Environmental exposure controls	: Avoid release to the environment.

#### 8.3. Individual protection measures, such as personal protective equipment

##### Hand protection:

Wear suitable gloves resistant to chemical penetration. Consult glove manufacturer's product information on material suitability and material thickness.

##### Eye protection:

Wear eye/face protection

##### Skin and body protection:

Wear suitable protective clothing

##### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. SDSs cannot provide detailed and complete respiratory protection guidelines. Selection of respiratory protection must be done by a qualified person who has assessed the work environment.

##### Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

### SECTION 9 Physical and chemical properties

#### 9.1. Basic physical and chemical properties

Physical state	: Liquid
Colour	: No data available
Odour	: No data available
Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 93.3 °C (200 °F)
Flammability (solid, gas)	: Not flammable

# Windshield Repair Kit – Resin 2

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Vapour pressure	: No data available
Relative vapour density at 20°C/ 68 °F	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Explosive limits	: No data available
Particle characteristics	: No data available

### 2-Propenoic acid

Boiling point	141 °C (at 1013 hPa)
Flash point	48.5 °C (closed cup)
Auto-ignition temperature	438 °C
Vapour pressure	3.8 hPa (at 20 °C)
Particle characteristics	No data available

### 2-Propenoic acid, (1R,2R,4R)-1,7,7-trimethylbicyclo[2.2.1]hept-2-ylester, rel-

Boiling point	275 °C Atm. press.: 1013 hPa
Flash point	104 °C Atm. press.: 1013 hPa
Vapour pressure	0.013 hPa (at 20 °C)
Particle characteristics	No data available

### 2-Hydroxyethyl methacrylate

Boiling point	213 °C (at 1013.25 hPa)
Flash point	106 °C (closed cup)
Vapour pressure	0.1 hPa (at 20 °C)
Particle characteristics	No data available

### Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate

Boiling point	> 350 °C (at 1013 hPa (no decomposition))
Flash point	92 °C (open cup)
Vapour pressure	0.000001 hPa (at 20 °C)
Particle characteristics	No data available

## 9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

## SECTION 10 Stability and reactivity

### 10.1. Reactivity

No dangerous reactions known under normal conditions of use.

# Windshield Repair Kit – Resin 2

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Heat. Incompatible materials.

### 10.5. Incompatible materials

Strong oxidizing agents.

### 10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon. Irritating vapours.

## SECTION 11 Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified.  
Acute toxicity (dermal) : Not classified.  
Acute toxicity (inhalation) : Not classified.

#### 2-Propenoic acid (79-10-7)

LD50 oral rat	193 mg/kg (Source: JAPAN_GHS)
LD50 oral	340 mg/kg
LD50 dermal rabbit	> 2000 mg/kg (Source: ECHA_API)
LD50 dermal	280 mg/kg
LC50 inhalation rat	11.1 mg/l (Exposure time: 1 h Source: JAPAN_GHS)

#### 2-Propenoicacid,(1R,2R,4R)-1,7,7-trimethylbicyclo[2.2.1]hept-2-ylester,rel- (5888-33-5)

LD50 oral rat	4890 mg/kg (Source: NLM_CIP)
LD50 dermal rabbit	> 3000 mg/kg bodyweight Animal: rabbit, Animal sex: male, Guideline: other:pre-guideline

#### 2-Hydroxyethyl methacrylate (868-77-9)

LD50 oral rat	5564 mg/kg (Source: ECHA)
LD50 dermal rabbit	> 5000 mg/kg (Source: ECHA)

#### Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)

LD50 oral rat	2615 mg/kg (Source: IUCLID)
Skin corrosion/irritation	: Causes skin irritation.

#### 2-Propenoic acid (79-10-7)

pH	2.63 (conc: 0.1 M (solution))
----	-------------------------------

Serious eye damage/irritation : Causes serious eye irritation.

#### 2-Propenoic acid (79-10-7)

pH	2.63 (conc: 0.1 M (solution))
----	-------------------------------

# Windshield Repair Kit – Resin 2

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Respiratory or skin sensitisation : May cause an allergic skin reaction.  
Germ cell mutagenicity : Not classified.

Carcinogenicity : Not classified.

### 2-Propenoic acid (79-10-7)

IARC group	3 - Not classifiable
------------	----------------------

Reproductive toxicity : Not classified.  
STOT-single exposure : Not classified.

### 2-Propenoic acid (79-10-7)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

### 2-Propenoic acid, (1R,2R,4R)-1,7,7-trimethylbicyclo[2.2.1]hept-2-ylester, rel- (5888-33-5)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

STOT-repeated exposure : Not classified.

### 2-Hydroxyethyl methacrylate (868-77-9)

LOAEC (inhalation, rat, gas, 90 days)	350 ppm Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study), Remarks on results: other:
NOAEC (inhalation, rat, gas, 90 days)	100 ppm Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study), Remarks on results: other:

Aspiration hazard : Not classified.

### Windshield Repair Kit – Resin 2

Viscosity, kinematic	No data available
----------------------	-------------------

### 2-Propenoic acid (79-10-7)

Viscosity, kinematic	1.094 mm <sup>2</sup> /s
----------------------	--------------------------

### Aliphatic urethane acrylate (143566-26-1)

Viscosity, kinematic	No data available
----------------------	-------------------

### 2-Propenoic acid, (1R,2R,4R)-1,7,7-trimethylbicyclo[2.2.1]hept-2-ylester, rel- (5888-33-5)

Viscosity, kinematic	No data available
----------------------	-------------------

### 2-Hydroxyethyl methacrylate (868-77-9)

Viscosity, kinematic	No data available
----------------------	-------------------

### Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)

Viscosity, kinematic	No data available
----------------------	-------------------

### Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidinyl ester (82919-37-7)

Viscosity, kinematic	No data available
Symptoms/effects after inhalation	: May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

# Windshield Repair Kit – Resin 2

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.

## SECTION 12 Ecological information

### 12.1. Ecotoxicity

Ecology - general	: May cause long-term adverse effects in the aquatic environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified.
Hazardous to the aquatic environment, long-term (chronic)	: Not classified.

### 2-Propenoic acid (79-10-7)

LC50 - Fish [1]	27 mg/l
EC50 - Crustacea [1]	95 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 72h - Algae [1]	0.04 mg/l (Species: Desmodesmus subspicatus)
EC50 96h - Algae [1]	0.17 mg/l (Species: Pseudokirchneriella subcapitata)
ErC50 algae	0.13 mg/l
LOEC (chronic)	8.1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	≥ 10.1 mg/l Test organisms (species): Oryzias latipes Duration: '45 d'
NOEC chronic algae	0.016 mg/l

### 2-Propenoic acid,(1R,2R,4R)-1,7,7-trimethylbicyclo[2.2.1]hept-2-ylester,rel- (5888-33-5)

LC50 - Fish [1]	0.704 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA)
EC50 72h - Algae [1]	1.98 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	0.596 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
LOEC (chronic)	0.277 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.092 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

### 2-Hydroxyethyl methacrylate (868-77-9)

LC50 - Fish [1]	213 – 242 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
EC50 - Crustacea [1]	380 mg/l Test organisms (species): Daphnia magna
LC50 - Fish [2]	227 mg/l (Exposure time: 96 h - Species: Pimephales promelas Source: IUCLID)
EC50 72h - Algae [1]	836 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	345 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
LOEC (chronic)	49.6 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	24.1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

### Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)

LC50 - Fish [1]	0.97 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
-----------------	---

# Windshield Repair Kit – Resin 2

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

### 12.2. Persistence and degradability

#### Windshield Repair Kit – Resin 2

Persistence and degradability	Not established.
-------------------------------	------------------

#### 2-Propenoic acid (79-10-7)

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

#### Aliphatic urethane acrylate (143566-26-1)

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

#### 2-Propenoic acid, (1R,2R,4R)-1,7,7-trimethylbicyclo[2.2.1]hept-2-ylester, rel- (5888-33-5)

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

#### 2-Hydroxyethyl methacrylate (868-77-9)

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

#### Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

#### Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidinyl ester (82919-37-7)

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

### 12.3. Bioaccumulative potential

#### Windshield Repair Kit – Resin 2

Bioaccumulative potential	Not established.
---------------------------	------------------

#### 2-Propenoic acid (79-10-7)

Partition coefficient n-octanol/water	0.46 (at 25 °C)
---------------------------------------	-----------------

#### 2-Propenoic acid, (1R,2R,4R)-1,7,7-trimethylbicyclo[2.2.1]hept-2-ylester, rel- (5888-33-5)

Partition coefficient n-octanol/water	4.52
---------------------------------------	------

#### 2-Hydroxyethyl methacrylate (868-77-9)

BCF - Fish [1]	1.34 – 1.54
----------------	-------------

Partition coefficient n-octanol/water	0.42 (at 25 °C (at pH >=5.9-<=6.1))
---------------------------------------	-------------------------------------

#### Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)

Partition coefficient n-octanol/water	0.37 (at 25 °C)
---------------------------------------	-----------------

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Ozone : Not classified.  
Fluorinated greenhouse gases : No

Other information : No other effects known.

# Windshield Repair Kit – Resin 2

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

### SECTION 13 Disposal considerations

Product/Packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### SECTION 14 Transport information

In accordance with DOT / TDG

#### 14.1. UN Number

UN-No. (DOT) : UN3082  
UN-No. (TDG) : UN3082

#### 14.2. UN Proper Shipping Name

Proper Shipping Name (DOT) : Environmentally hazardous substances, liquid, n.o.s. (2-Propenoicacid,(1R,2R,4R)-1,7,7-trimethylbicyclo[2.2.1]hept-2-ylester,rel-)  
Proper Shipping Name (TDG) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-Propenoicacid,(1R,2R,4R)-1,7,7-trimethylbicyclo[2.2.1]hept-2-ylester,rel-)

#### 14.3. Transport hazard class(es)

##### DOT

Transport hazard class(es) (DOT) : 9  
Hazard labels (DOT) : 9



##### TDG

Transport hazard class(es) (TDG) : 9  
Hazard labels (TDG) : 9



#### 14.4. Packing group

Packing group (DOT) : III  
Packing group (TDG) : III

#### 14.5. Environmental hazards

Marine pollutant : Yes (IMDG only)



Other information : No supplementary information available.

#### 14.6. Transport in bulk

Not applicable

# Windshield Repair Kit – Resin 2

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

### 14.7. Special precautions for user

Special transport precautions

: Do not handle until all safety precautions have been read and understood.

#### DOT

UN-No. (DOT)

DOT Special Provisions (49 CFR 172.102)

: UN3082

: 8 - A hazardous substance that is not a hazardous waste may be shipped under the shipping description "Other regulated substances, liquid or solid, n.o.s.", as appropriate. In addition, for solid materials, special provision B54 applies.

146 - This description may be used for a material that poses a hazard to the environment but does not meet the definition for a hazardous waste or a hazardous substance, as defined in 171.8 of this subchapter, or any hazard class as defined in Part 173 of this subchapter, if it is designated as environmentally hazardous by the Competent Authority of the country of origin, transit or destination.

173 - An appropriate generic entry may be used for this material.

335 - Mixtures of solids that are not subject to this subchapter and environmentally hazardous liquids or solids may be classified as "Environmentally hazardous substances, solid, n.o.s," UN3077 and may be transported under this entry, provided there is no free liquid visible at the time the material is loaded or at the time the packaging or transport unit is closed. Each transport unit must be leakproof when used as bulk packaging.

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling =  $97 / (1 + a (tr - tf))$  Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx)

: 155

DOT Packaging Non Bulk (49 CFR 173.xxx)

: 203

DOT Packaging Bulk (49 CFR 173.xxx)

: 241

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)

: No Limit

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)

: No Limit

DOT Vessel Stowage Location

: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

#### TDG

UN-No. (TDG)

: UN3082

# Windshield Repair Kit – Resin 2

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

TDG Special Provisions	: 16 - (1) The technical name of at least one of the most dangerous substances that predominantly contributes to the danger or dangers posed by the dangerous goods must be shown, in parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(ii)(A). The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and (3). (2) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a shipping document or on a small means of containment when Canadian law for domestic transport or an international convention for international transport prohibits the disclosure of the technical name: (a) UN1544, ALKALOID SALTS, SOLID, N.O.S. or ALKALOIDS, SOLID, N.O.S; (b) UN1851, MEDICINE, LIQUID, TOXIC, N.O.S; (c) UN3140, ALKALOID SALTS, LIQUID, N.O.S. or ALKALOIDS, LIQUID, N.O.S; (d) UN3248, MEDICINE, LIQUID, FLAMMABLE, TOXIC, N.O.S; or (e) UN3249, MEDICINE, SOLID, TOXIC, N.O.S. (3) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a small means of containment: (a) UN2814, INFECTIOUS SUBSTANCE, AFFECTING HUMANS; or (b) UN2900, INFECTIOUS SUBSTANCE, AFFECTING ANIMALS,99 - (1) Mixtures of solids that are not dangerous goods and liquids or solids that are UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S, or UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S, may be offered for transport, handled or transported as UN3077 if there is no visible liquid when the dangerous goods are loaded into a means of containment and during transport. (2) These Regulations, except for Parts 1 and 2, do not apply to the offering for transport, handling or transport of less than 450 kg of UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S, or less than 450 L of UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S, on a road vehicle or a railway vehicle. The dangerous goods must be contained in one or more small means of containment designed, constructed, filled, closed, secured and maintained so that under normal conditions of transport, including handling, there will be no release of the dangerous goods that could endanger public safety.
Explosive Limit and Limited Quantity Index	: 5 L
Excepted quantities (TDG)	: E1
Emergency Response Guide (ERG) Number	: 171

## SECTION 15 Regulatory information

### 15.1. Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories

### 15.2. International regulations

No additional information available

# Windshield Repair Kit – Resin 2

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

### 15.3. State regulations

**⚠️ WARNING:** This product can expose you to Methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### SECTION 16 Other Information

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Revision date : 2025-03-19  
Issue date : 2025-02-19  
Other information : None.  
Prepared by : Nexreg Compliance Inc.  
[www.Nexreg.com](http://www.Nexreg.com)



#### Indication of changes:

Section	Changed item	Comments	Version
SDS	SDS update	Modified	V 2.0

SDS HazCom 2024 - WHMIS 2022 (Nexreg) 2025

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.