

Safety Data Sheet

Revision Date 05-24-2015
Revision Number 1

SECTION 1 Identification of the substance/mixture and of the company/undertaking

Product identification used on label

Product identifier	1656 YEL Rust Inhibiting Compound Clear
Details of the supplier of the safety data sheet	YEL Company 11210 Katherine's Crossing, Suite 100 Woodridge, IL 60517 630-754-4200
Emergency telephone number	Chemtrec: (800) 424-9300
Relevant identified uses of the substance or mixture and uses advised against	Corrosion Preventive Compound

SECTION 2 Hazards identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Hazard Symbols



GHS Classification	Skin Corrosion/Irritation Category 2 Serious Eye Damage/Eye Irritation Category 2B Flammable Liquid Category 3 Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 3
Signal Word	Warning
Hazard Statements	Flammable liquid and vapor. Causes skin and eye irritation May cause respiratory irritation. May cause drowsiness or dizziness.
Precautionary Statements	
Prevention	Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Ground/bond container and receiving equipment. Use explosion-proof equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapours/spray.

Safety Data Sheet

Revision Date 05-24-2015
Revision Number 1

Wash thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.

Response IF ON SKIN: Wash with plenty of soap and water.
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Call a POISON CENTER or doctor/physician if you feel unwell.
Specific treatment: None known
If skin irritation occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
Take off contaminated clothing and wash before reuse.
Use dry chemical, water fog, CO₂, foam or sand/earth for extinction.

Storage Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulation for hazardous wastes.

SECTION 3 Composition/information on ingredients

Chemical Name	CAS #	%
Hydrotreated light distillate (Petroleum)	64742-47-8	15 - 40

Note: Specific chemical identities and/or exact percentages have been withheld as a trade secret.

SECTION 4 First aid measures

Inhalation If symptoms are experienced remove source of contamination or move victim to fresh air and obtain medical advice.

Eyes Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention.

Skin Contact Wash with soap and water. Get medical attention if irritation develops or persists.

Ingestion Do not induce vomiting and seek medical attention immediately. Provide medical care provider with this SDS.

Note to Doctor Treat symptomatically.

Safety Data Sheet

Revision Date 05-24-2015
Revision Number 1

SECTION 5 Firefighting measures

Extinguishing media Use alcohol resistant foam, carbon dioxide, dry chemical, or water spray when fighting fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the fire. Do not direct a water stream directly into the hot burning liquid.

Fire and/or Explosion Hazards Vapors may be ignited by sparks, flames or other sources of ignition if material is above the flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back. Empty containers that retain product residue (liquid, solid/sludge, or vapor) can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. Any of these actions can potentially cause an explosion that may lead to injury or death.

Fire Fighting Methods and Protection Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Use appropriate methods for the surrounding fire.

Hazardous Combustion Products Smoke, Oxides of carbon, Calcium oxides, Sulfur oxides

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures No health effects expected from the clean-up of this material, if contact can be avoided. Follow personal protective equipment recommendations found in Section VIII of this SDS

Methods and materials for containment and cleaning up Absorb or cover with dry earth, sand or other non-combustible material and transfer to appropriate waste containers. Use clean, non-sparking tools to collect absorbed material. Collect and discard in accordance with local, state and national regulations. Use an inert absorbent such as sand or vermiculite. Place in properly labeled closed container.

SECTION 7 Handling and storage

Safety Data Sheet

Revision Date 05-24-2015
Revision Number 1

Precautions for safe handling

Mildly irritating material. Avoid unnecessary exposure. As with all chemicals, good industrial hygiene practices should be followed when handling this material. Wash thoroughly after handling. Do not get in eyes, on skin and clothing. Ground and bond containers when transferring material. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Use with adequate ventilation Follow all SDS/label precautions even after container is emptied because it may retain product residues

Conditions for safe storage, including any incompatibilities

Store in a cool dry place. Isolate from incompatible materials. Keep container closed when not in use. Keep away from heat, sparks, and flame. Limit quantity of material stored. Do not store in direct sunlight

Incompatible materials

Strong oxidizing agents, Acids

SECTION 8 Exposure controls/personal protection

Control parameters

Chemical Name

ACGIH TLV

ACGIH STEL

OSHA PEL

Hydrotreated light distillate
(Petroleum)

212 ppm (8 hrs)

Engineering Measures

Local exhaust ventilation or other engineering controls are normally required when handling or using this product to avoid overexposure. Engineering controls must be designed to meet the OSHA chemical specific standard in 29 CFR 1910. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits

Respiratory Protection

Proper ventilation (at a minimum) will be required when handling this product. Use respirators (NIOSH approved) only if ventilation cannot be used to eliminate symptoms or reduce the exposure to below acceptable levels. Follow a respiratory protection program that meets 29 CFR 1910.134 and ANSI Z88.2 requirements whenever work place conditions warrant the use of a respirator.

Eye Protection

Wear chemically resistant safety glasses with side shields when handling this product. Do not wear contact lenses.

Safety Data Sheet

Revision Date 05-24-2015

Revision Number 1

Skin Protection Not normally considered a skin hazard. Where use of product can result in skin contact, practice good personal hygiene and wear a barrier cream and/or impervious surgical style gloves. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work.

Gloves Chemically resistant gloves

SECTION 9 Physical and chemical properties (Typical, not specification)

Physical State	Viscous Liquid
Color	Amber
Odor	Petroleum Type
Odor Threshold	No data available
pH	No data available
Melting Point, °C	No data available
Boiling Point, °C	No data available
Flash Point	>= 104 °F(40 °C)
Evaporation Rate	No data available
Flammability (Solid, Gas)	No data available
Lower Flammable/Explosive Limit, % in air	No data available
Upper Flammable/Explosive Limit, % in air	No data available
Vapor Pressure	3.4 mmHg
Vapor Density	>1 (Air=1)
Specific Gravity @ 25°C	0.89
Solubility in Water	Negligible; 0-1%
Octanol/Water Partition Coefficient	No data available

Safety Data Sheet

Revision Date 05-24-2015
Revision Number 1

Autoignition Temperature	No data available
Decomposition Temperature	No data available
Viscosity	Typical 5000 cP
Volatiles, % by weight	51
VOC, lb/gal	3.3
VOC, grams/liter	395.8
VOC minus exempt solvents & water, lb/gal	3.3

SECTION 10 Stability and reactivity

Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	Contamination. Elevated temperatures. Contact with air. Visible light
Incompatible materials	Strong oxidizing agents, Acids
Hazardous decomposition products	Decomposition and hazardous decomposition products are unlikely.

SECTION 11 Toxicological information

Likely Routes of Entry	Inhalation, Skin contact, Eye contact, Absorption
Target Organs Potentially Affected by Exposure	Central Nervous System, Lungs (only if dust or mist is present), Skin, None known, Eyes
Chemical Interactions That Change Toxicity	No chemical interaction known to affect toxicity.
Medical Conditions Aggravated	Skin contact may aggravate existing skin disease, Respiratory disease including asthma and bronchitis

Immediate (Acute) Health Effects by Route of Exposure

Inhalation Irritation	Can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache. Other possible symptoms include; wheezing and coughing due to pulmonary edema (fluid build-up in lungs).
Skin Contact	Can cause minor skin irritation, defatting, and dermatitis.
Skin Absorption	Minimal hazard in normal industrial use. May cause gastrointestinal discomfort
Eye Contact	Can cause moderate irritation, tearing and reddening, but not likely to permanently injure eye tissue.
Ingestion Irritation	Irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea, vomiting and diarrhea. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal.

Safety Data Sheet

Revision Date 05-24-2015
Revision Number 1

Ingestion Toxicity Harmful if swallowed.

Long-Term (Chronic) Health Effects

Carcinogenicity Not listed by ACGIH, IARC, NIOSH, NTP OR OSHA.

Reproductive and Developmental Toxicity No data available to indicate product or any components present at greater than 0.1% may cause birth defects.

Inhalation Upon prolonged and/or repeated exposure, can cause severe respiratory irritation, dizziness, weakness, fatigue, nausea, headache and possible unconsciousness. Can cause systemic damage upon prolonged and/or repeated exposure (see "Target Organs")

Skin Contact Upon prolonged or repeated contact, can cause minor skin irritation, defatting, and dermatitis.

Skin Absorption Upon prolonged or repeated exposure, minimal hazard in normal industrial use. May cause gastrointestinal discomfort.

Component Toxicology Data

Chemical Name	CAS Number	LD50/LC50
Hydrotreated light distillate (Petroleum)	64742-47-8	Dermal LD50 Rabbit > 5000 mg/kg Oral LD50 Rat > 5000 mg/kg Inhalation LC50 (4h) Rat > 20 mg/L

SECTION 12 Ecological information

Overview	No ecological information available
Mobility	No data
Persistence	No data
Bioaccumulation	No data
Degradability	No data

Ecotoxicity Data

Chemical Name	CAS Number	Aquatic EC50 Crustacea	Aquatic ERC50 Algae	Aquatic LC50 Fish
No data available				

SECTION 13 Disposal considerations

Waste Description for Spent Product	Spent or discarded material may be a hazardous waste.
Disposal Methods	Dispose of by incineration following Federal, State, Local, or Provincial regulations.
Waste Disposal Code(s)	D001

Safety Data Sheet

Revision Date 05-24-2015
Revision Number 1

SECTION 14 Transport information

Full shipping name for Export, Air, Sea (any quantity unless flash pt. >150°F) or vessels of 119 GL or more UN1268, PETROLEUM DISTILLATES, N.O.S., (Naphtha Solvent), 3, PG III,
Domestic Ground in vessels < 119 gal. Not Regulated

SECTION 15 Regulatory information

TSCA Status All components in this product are on the TSCA Inventory or exempt.

Canadian DSL status: One or more chemical substances in this material are on the Canadian NDSL and the remainder are included on the Canadian DSL or are exempt.

Chemical Name	CAS #	Regulation	Percent
No 313-listed chemicals in this product		SARA 313	

SECTION 16 Other information

Revision Date 05-24-2015

Disclaimer Although the information contained herein is believed to be reliable, it is furnished without warranty of any kind. This information is not intended to be all-inclusive as to the manner and conditions of use, handling, and storage.

Version Original

Comments Approved: M. Longo / M. Duncan